



Vinyl Stair Treads

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Vinyl Stair Treads ADA Compliant

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkett.com


1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Vinyl Stair Treads are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants to meet the performance requirements of ASTM F 2169 Standard Specification for Resilient Stair Treads, Type TV, Class 2, Group 1 and 2. Tarkett Vinyl Stair Treads are available with a 2" (5.08 cm) wide carborundum strip or co-extruded strip (VIHD only) of contrasting color to comply with A.D.A., Visually-Impaired, and California Title 24 Accessibility requirements.


Tarkett Vinyl Stair Treads are designed for interior applications only and not recommended for commercial kitchen environments.

1.3.2. **Styles & Physical Characteristics:**


HD Square Nose:




HT Square Nose:




HT Round Nose:



ST Square Nose:



ST Round Nose:



2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A

2.2. **Abrasion Resistance** (ASTM D 3389): 0.22 mg/cycle

2.3. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.4. **Fire Resistance** (ASTM E 648/NFPA 253 - Critical Radiant Flux): Class 1

2.5. **Smoke Development** (ASTM E 662/NFPA 258): less than 450

2.6. **CAN/ULC S102.2:** FSR 70 / SDC 555

3. INSTALLATION

See Stair Tread installation instructions for complete details.

3.1. **Adhesives:**

• **Tarkett 965 Adhesive Coverage:**

Porous Substrate: 1/16x1/16x1/16 SQ-notch – 125-150 sq. ft. per gallon

Non-porous Substrate: 1/16x1/16x1/16 V-notch – 150-175 sq. ft. per gallon

• **Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush or roller

Approximate coverage:

1 quart unit (0.95 liters) – 24 to 36 sq. ft.

1 gallon unit (3.79 liters) – 144 to 215 sq. ft.

• **Tarkett 930 Two-Part Epoxy Caulking Compound**

Application: 13.5 oz. cartridge, with #530 Caulking Gun at a 1/4" diameter bead approximately 50 linear feet.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Stairwell Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (800) 899-8916 or E-mail:

Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com



Vinyl Stair Treads

Product Specification

Tread Type	Product Code	Overall Depth	Gauge Tapering Thickness	Nose Type	Nominal Length*	Pieces Per Carton	Weight Per Ft.
SERVICE WEIGHT	ST	12"	5/32" to 5/64"	RD./SQ.	3', 3.5', 4', 6', 8', 12'	10 pcs.	1 lb.
						5 pcs. (12' Lengths Only)	
SAFE - T - RIB	HT	12 1/4"	1/4" to 1/8"	RD./SQ.	3', 3.5', 4', 6', 8', 12'	5 pcs.	1 1/2 lbs.
HEAVY DUTY	HD	12 1/4"	1/4" to 7/32"	SQ.	3', 3.5', 4', 6', 8', 12'	5 pcs.	1 3/4 lbs.
HOUSEHOLD (AVAILABLE IN COLORS: 40 BLACK AND 47 BROWN ONLY.)	HH	9 3/16"	Standard	RD./SQ.	1 1/2', 2', or 3'	36 pcs.	3/4 lbs.
VISUALLY IMPAIRED SAFE-T-GRIP	VIVG	12 1/4"	1/4" to 1/8"	SQ.	3', 3.5', 4', 6', 8', 12'	5 pcs.	1 1/4 lbs.
VISUALLY IMPAIRED SAFE - T - RIB	VIHT	12 1/4"	1/4" to 1/8"	RD./SQ.	3', 3.5', 4', 6', 8', 12'	5 pcs.	1 1/2 lbs.
VISUALLY IMPAIRED HEAVY DUTY	VIHD	12 1/4"	1/4" to 7/32"	SQ.	3', 3.5', 4', 6', 8', 12'	5 pcs.	1 3/4 lbs.
How to Order: [Product Code] – [Color Code] – [Length] – [Nose Type] (Example: ST 47 4 SQ)							

*NOTE: In applications where the staircase is the same width as Tarkett Stair Treads, Nosings, Risers, and Stringers, order the next size up to allow for proper installation.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com

© 2022 Tarkett USA Inc. 11/2022