

Safety Data Sheet**TARKETT JOHNSONITE 906**

Safety Data Sheet dated: 3/20/2015 - version 1

Date of first edition: 3/20/2015

1. IDENTIFICATION**Product identifier**

Mixture identification:

Trade name: **TARKETT JOHNSONITE 906****Other means of identification:**

Trade code: 2228

Recommended use of the chemical and restrictions on use

Recommended use: Adhesive

Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Tarkett USA Inc., 30000 Aurora Rd., Solon, OH 44139

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-613-996-6666

2. HAZARD(S) IDENTIFICATION**Classification of the chemical****Classification of the chemical**

Carc. 1A May cause cancer.

STOT RE 1 Causes damage to organs through prolonged or repeated exposure.

Label elements**Symbols:**

Danger

Code	Description
H350.1	May cause cancer.
H372.2	Causes damage to organs through prolonged or repeated exposure.
Code	Description
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260.B	Do not breathe dust.
P264.3	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280.I	Wear protective gloves and eye protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P405	Store locked up.
P501.A	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

Additional classification information



HMIS Health: 1 = SLIGHT
HMIS Health - Is health hazard chronic?: Yes
HMIS Flammability: 1 = Combustible if heated
HMIS Reactivity: 0 = MINIMAL
HMIS P.P.E.: Safety glasses, gloves
NFPA Health: 1 = SLIGHT
NFPA Flammability: 1 = Combustible if heated
NFPA Reactivity: 0 = MINIMAL
NFPA Special Risk: N.A.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Quantity	Name	Ident. Numb.	Classification
3-7 %	Silica Sand	CAS:14808-60-7	Carc. 1A, H350.A; STOT RE 1, H372.A
0.1-1 %	Petroleum distillate	CAS:64742-46-7	Acute Tox. 4, H332; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Aquatic Chronic 2, H411

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

N.A.

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
Silica Sand	ACGIH			0,025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;

Appropriate engineering controls: N.A.

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State: Liquid
Appearance and colour: Paste black
Odour: Latex like
Odour threshold: N.A.
pH: 8.00
Melting point / freezing point: N.A.
Initial boiling point and boiling range: >100 °C (212 °F)
Flash point: >100 °C (212 °F)
Evaporation rate: Same as water
Upper/lower flammability or explosive limits: N.A.
Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.15 g/cm3
Solubility in water: N.A.
Solubility in oil: N.A.

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Quantity	Component	Ident. Numb.	Ecotox Infos
3-7 %	Silica Sand	CAS: 14808-60-7	LC50 a) Aquatic acute toxicity carp> 10000,00000mg/L 72h
0.1-1 %	Petroleum distillate	CAS: 64742-46-7	LC50 a) Aquatic acute toxicity Fish Pimephales promelas= 35mg/L 96h IUCLID Flow-Through LC50 a) Aquatic acute toxicity Pimephales> 10000,00000mg/L 96h Static LC50 a) Aquatic acute toxicity Fish Pimephales promelas= 35mg/L 96h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

14. TRANSPORT INFORMATION

UN number

ADR-UN number: N/A

DOT-UN Number: N/A

IATA-Un number: N/A

IMDG-Un number: N/A

UN proper shipping name

ADR-Shipping Name: N/A

DOT Proper Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

Transport hazard class(es)

ADR-Class: N/A

DOT Hazard Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

Packing group

ADR-Packing Group: N/A

DOT-Packing group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): N/A

DOT Label(s): N/A

DOT Symbol: N/A

DOT Cargo Aircraft: N/A

DOT Passenger Aircraft: N/A

DOT Bulk: N/A
DOT Non-Bulk: N/A
Road and Rail (ADR-RID):
ADR-Label: N/A
ADR - Hazard identification number: N/A
ADR Tunnel Restriction Code: N/A

Air (IATA):
IATA-Passenger Aircraft: N/A
IATA-Cargo Aircraft: N/A
IATA-Label: N/A
IATA-Subrisk: N/A
IATA-Erg: N/A
IATA-Special Provisions: N/A

Sea (IMDG):
IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A
IMDG-Subrisk: N/A
IMDG-Special Provisions: N/A
IMDG-Page: N/A
IMDG-Label: N/A
IMDG-EMS: N/A
IMDG-MFAG: N/A

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Silica Sand	is listed in TSCA	Section 8b
Petroleum distillate	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

no substances listed

Section 304 - Hazardous substances:

no substances listed

Section 313 - Toxic chemical list:

no substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

no substances listed

CAA - Clean Air Act

CAA listed substances:

no substances listed

CWA - Clean Water Act

CWA listed substances:

no substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Silica Sand	Listed as carcinogen
-------------	----------------------

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Silica Sand

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Silica Sand

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Silica Sand

16. OTHER INFORMATION

Code	Description
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H350.1	May cause cancer.
H350.A	May cause cancer if inhaled.
H372.2	Causes damage to organs through prolonged or repeated exposure.
H372.A	Causes damage to organs through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet dated: 3/20/2015 - version 1

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.