

RUBY 70

## THE COST EFFECTIVE SOLUTION WITH TOP PERFORMANCE QUALITIES

Accent Excellence 70 Ruby is a cost-effective safety floor with premium qualities. The collection includes a range of designs inspired by nature, including realistic wood designs in both soft and dark grain hues, and a range of timeless mineral patterns in an assortment of sophisticated

colours. This floor includes a special grip to help protect against slips and falls, making it ideal for heavy traffic areas requiring extra safety. It is treated with our trademarked Top Clean XP surface protection for extreme durability and cost-effective maintenance.

### PERFORMANCE AND SAFETY:

- 0.7mm wear layer reinforced with TopClean™ PUR surface treatment for excellent resistance to indentation, abrasion, scuffing, scratches and stains.
- P3/R10 slip performance ideal for heavy traffic areas

### SAFE CHOICE FOR THE ENVIRONMENT:

- TopClean™ reinforced PUR surface coating guarantees easy cleaning with less need for water and detergent, reducing the impact of cleaning chemicals on the environment
- No wax no polish throughout its lifetime, significantly reducing use of water, energy and chemical detergents, stain and scratch resistant
- Phtalate free technology for healthy environments.
- TVOC ≤ 100 µg/m³ for good indoor air quality.



HETEROGENEOUS COMPACT VINYL

## RUBY 70

### SPECIFICATIONS

Printed compact vinyl floorcovering on a glass fiber stabilized carrier, filler free wear layer.

PUR reinforcement, built with a fungistatic and bacteriostatic Sanitized® treatment.

Product standard ISO 10582 - EN 649.

PRODUCT CHARACTERISTICS	STANDARDS	RUBY 70
Product construction	EN ISO 10582	Heterogeneous compact vinyl flooring
Classification	EN ISO 10874	Commercial: 34; Industrial: 43
Surface treatment		TopClean™ PUR
Total thickness	EN ISO 24346	2.0mm
Wear layer thickness	EN ISO 24340	0.7mm
Total weight	EN ISO 23997	3000 g/m²
Form of delivery	EN ISO 24341	Approx. 23Lm x 2m
Warranty		10 years
Underfloor heating		Suitable
Colours		19

PERFORMANCE CHARACTERISTICS	STANDARDS	RUBY 70
Reaction to fire	EN ISO 9239-1	Critical radiant flux 8.2 kW/m². Smoke 193%.min
Slip resistance	AS 4586/ DIN 51130*	P3/R10
Electrostatic Properties	EN 1815/ EN 1081	< 2 kV on concrete/ R1 > 10 <sup>9</sup> Ω
Total VOC emissions	AgBB/DIBt	≤ 100 µg/m³ (after 28 days)
Thermal resistance	EN 12667	0.02 m² K/W
Chemical resistance	EN IS 26987	High resistance
Dimensional stability	EN ISO 23999	≤ 0.10%
Wear-layer binder content	EN ISO 10582	Type I
Residual indentation	EN ISO 24343-1	≤ 0.02mm
Castor chair test	ISO 4918	No damage
Furniture leg test	EN 424	No damage
Curl resistance to heat	EN ISO 23999	≤ 8mm
Light fastness	EN ISO 105-B02	≥ level 6

\* DIN 51130.2004 and 2010 is equivalent to Appendix D AS 4586.2013

Tarkett's instruction regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



### A RANGE OF COORDINATED WELDING RODS

RUBY 70	WELDING ROD N°	RUBY 70	WELDING ROD N°	RUBY 70	WELDING ROD N°
029	1287 285	052	1287 443	076	1287 733
034	1292 101	063	1287 174	077	1294 429
035	1294 428	068	1287 516	078	1287 685
036	1287 713	072	1287 333	079	1287 517
045	1287 308	073	1294 852	109	1287 385
046	1287 526	074	1287 505		
049	1287 435	075	1287 153		

Tarkett Australia Pty Ltd  
Suite 1, Level 3, 3 Columbia Court  
Baulkham Hills 2153  
www.tarkospec.com.au



Tarkett

RUBY 70

HETEROGENEOUS COMPACT VINYL

## Ruby 70

HETEROGENEOUS COMPACT VINYL



# RUBY 70

## WOOD



Hetre Fayard Light Natura 2509 8029



Faro 2 Warm Beige 2509 8073



Faro 2 Natural 2509 8034



Oak Natural Honey 2509 8075



Oak Beige 2509 8076



Oak Middle Beige 2509 8035



Oak Middle Natural 2509 8074



Oak Dark Brown 2509 8077



Oak Grey 2509 8036



Faro 2 Anthracite 2509 8072



## NATURE



Warm Medium Grey 2509 8049



Cold Dark Grey 2509 8045



Black 2509 8046



Dark Blue 2509 8109

