



HOMOGENEOUS COMPACT VINYL

# Wallgard

Wall protection  
for optimal hygiene

# Wallgard



## DESIGN FLEXIBILITY

### EXTENSIVE COLOUR OFFER IN SOFT, MODERN PATTERN

- Colours ranging from white to pastel tones for selection of varying shades within same collection.

### CONTRAST COLOURS

- Colours which provide > 30 % difference in luminance between sanitary-ware and wall covering for people with visual disabilities.

## BEST IN CLASS FUNCTIONAL PERFORMANCE

### SEALED AND SMOOTH SURFACE FOR OPTIMAL HYGIENE

- Impervious surface with PU-Shield for high resistance against stains and chemicals. Does not contribute to infection spreading.

### IDEAL FOR SENSITIVE ENVIRONMENTS IN HEALTHCARE

- Reduces the level of environmental pollutants and guarantees a controlled level of contamination. Clean room approved.

### ENHANCED PROTECTION AGAINST FIRE

- Classified Group 1 in accordance with AS 3837

## PEOPLE FRIENDLY

### IMPROVED INDOOR ENVIRONMENT AND AIR QUALITY

- Extremely low VOC emissions 100 times lower than the strictest standards in Europe.
- The phthalate-free plasticizers selected by Tarkett are approved for food contact containers and can be used for toys intended to be placed in the mouth by children.

## EASY TO INSTALL

### HORIZONTAL OR VERTICAL INSTALLATION

- Excellent hot welding seam strength.
- 2 m width reducing the number of joints.

### UNIQUE FLEXIBILITY FOR WATERTIGHT FINISH

- Approved for use in wetrooms.

### WIDE RANGE OF ACCESSORIES TO PROVIDE THE PERFECT FINISH

- Flexible junction profile to reduce thickness difference between floor and wall covering for a perfect junction.

Coloured White	White Grey	21055 221	Coloured White	White Beige	21055 223	Strong Pastel	Yellow	21055 228
Strong Pastel	Green	21055 229	Coloured White	White Green	21055 225	Coloured White	White Yellow	21055 224
Coloured White	White Blue	21055 226	Coloured White	White Grey Beige	21055 222	Coloured White	White	21055 220 also available in 2.0mm thickness, product code no. 3105 025
Contrast Colour	Contrast Blue	21055 232	Strong Pastel	Blue	21055 230	Strong Pastel	Orange	21055 227
			Contrast Colour	Contrast Grey	21055 231			

Due to limitations in printing processes the colours represented here may vary, we recommend you refer to a physical sample.

# Wallgard

## Specification

Homogeneous heavy duty wall covering. Unique PU-Shield surface for better hygiene and cleanliness. Subtle and discreet design in modern colour. Can be installed vertically or horizontally. Heat welded seams with colour co-ordinated rods.

CERTIFICATION & CLASSIFICATION	STANDARDS	Wallgard
Type of wall covering		Homogeneous vinyl wall covering
CE certification	EN 15102	Yes
ISO certification		Ronneby ISO 9001/Ronneby ISO 14001
TECHNICAL CHARACTERISTICS	STANDARDS	Wallgard
PU-Shield		Yes
Total thickness	ISO 24346 - EN 428	1.3 mm
Total weight/m <sup>2</sup>	ISO 23997 - EN 430	2,100 g
Form of delivery	ISO 24341 - EN 426	
	Sheet	Approx. 30 lm x 200 cm
	(rolls)	Product no. 21055 _ _ _ 3 digit colour number
TECHNICAL PERFORMANCES	STANDARDS	Wallgard
Dimensional stability	ISO 23999 - EN 434	≤ 0.40%
Reaction to fire	AS/NZS 3837	Group 1 Average specific extinction area: 125.8m <sup>2</sup> /kg
Wetroom approval	GBR Class VT	Approved
Airborne particle emissions	ISO 14644-1 ASTM F24 F51	ISO class 4 Class A
Total VOC emissions	ISO 16000-6 AgBB/DIBt	≤ 10 µg/m <sup>3</sup> (after 28 days) Confirm
Outgassing VOC (23°C/90°C)	ISO-Accm class	≤ 9.6
Light fastness	EN ISO 105-B02	≥ level 7
Chemical resistance	ISO 26987 - EN 423	Excellent
Bacteria resistance	ISO 846: Part C	Does not favour growth
Seam strength	EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
Colours		13

The above information is subject to modification for the benefit of further improvement. (01/16).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

### Matching Weld Rods

Product No.	Welding Rod No.	Product No.	Welding Rod No.	Product No.	Welding Rod No.	Product No.	Welding Rod No.
220	1290 011	224	1287 723	228	1287 725	232	1287 724
221	1288 125	225	1287 726	229	1287 721		
222	1287 728	226	1288 157	230	1287 727		
223	1287 729	227	1287 722	231	1287 730		

### Recommended specification clause for your project

Tarkett Wallgard product number 21055\_\_\_\_\_

- 1.3mm thick homogenous 2m wide vinyl wall covering
- Phthalate free, TVOC below 10µg/m<sup>3</sup>
- Reaction to Fire Group 1 (AS/NZS3837)
- Approved to wetroom GBR Class VT or better
- Clean room test to satisfactory to ASTM F24/65 and to Class A to ASTM 51/100
- Where Wallgard is to be used as a waterproof membrane, it must be installed in accordance with the requirements of Tarkett Codemark Certificate CM30035
- Manufactured in plant with certification ISO 9001, ISO 14001 and OHSAS 18001
- 10 year commercial manufacturer's product warranty
- Must be installed as per manufacturer's instructions and as per AS 1884 with multicoloured weldrod on seams/joins

Our Sustainability tag explains the content of our products and how they contribute to our sustainability strategy and human well-being.



**For more detailed technical information, please contact Tarkett on 1300 851 484**