

Somplan 350

HOMOGENEOUS COMPACT VINYL FLOORCOVERING

Compact
Vinyl
solution for
heavy-traffic
areas



 **Tarkett**

Somplan 350

Somplan 350 is a homogeneous vinyl floorcovering suitable for heavy traffic in premises such as healthcare facilities and other commercial areas.

Key features:

- NEW! TEKANIUM™ Improved PU Performance
- High resistance to wear, compression, stain and bacteria
- Phthalate-free plasticizers for people's health and safety
- Extremely low TVOC emission ensuring high indoor air quality
- Available in 30 elegant colours combined with soft textures to provide a peaceful atmosphere




TEKANIUM™




Somplan 350






Green

© 306007 012




Light Green

© 306007 025




Middle Green

© 306007 026




Deep Green

© 306007 037




Grass Green

© 306007 036




Light Green Blue

© 306007 031




Peaceful Blue

© 306007 008




Sunny Blue

© 306007 029




Middle Blue

© 306007 024




Middle Warm Blue

© 306007 032




White Neutral

© 306007 030




Light Blue Grey

© 306007 002




Light Neutral Grey

© 306007 038




Middle Warm Grey

© 306007 018




Light Cool Grey

© 306007 016



Neutral Grey

© 306007 039



Middle Cool Grey

© 306007 017



Light Grey

© 306007 040



Light Beige

© 306007 004



Light Warm Beige

© 306007 021



ROLL

Somplan 350

Middle Warm Beige



© 306007 019

Middle Beige



© 306007 041

Light Yellow



© 306007 027

Middle Yellow



© 306007 006

Dark Warm Beige



© 306007 028

Dark Orange




© 306007 022

Pink




© 306007 034

Pastel Purple




© 306007 035

Purple



© 306007 033

Red



© 306007 023



ROLL

Somplan 350



Somplan 350

TECHNICAL DATA	STANDARD	SOMPLAN 350
CLASSIFICATION		
Type of Floorcovering	ISO 10581	Homogeneous
Classification	ISO 10874	Classes:
	Commercial	34
	Industrial	43
TECHNICAL CHARACTERISTICS		
Total thickness	ISO 24346	2.0mm
Dimension - Length	ISO 24341	23lm
Dimension - Width	ISO 24341	2m
Total weight	ISO 23997	3150g/m ²
Surface treatment		TEKTANIUM™
Binder content	ISO 10581	Type II
TECHNICAL PERFORMANCES		
Dimensional stability	ISO 23999	≤ 0.40% (Rolls)
Curl resistance to heat	ISO 23999	≤ 4.00mm
Reaction to fire	EN 13501-1	Bfl -s1
Residual indentation	ISO 24343-1 - measured value	≤ 0.03mm
	Required value	≤ 0.10mm
Castor chair test	ISO 4918 - EN 425	No damage
Thermal resistance	EN ISO 10456	0.04 (m ² ·K)/W
Light fastness	ISO 105 B02	≥ 6
Chemical resistance	ISO 26987	Good resistance
Slip resistance	DIN 51130	R9
Dynamic coefficient friction	EN 13893	μ≥ 0.3
Static electrical charge	EN 1815	≤ 2kV
Bacteria resistance	ISO 846-C	Doesn't favour growth
Flexibility	ISO 24344	20 mm – No crack
Clean room	ISO 14644-1	-
ENVIRONMENT		
TVOC 28 days	ISO 16000	< 10ug/m ³
Recyclable		100%
Plasticizer		Phthalate-free technology



www.tarkett-asia.com
Contact: saleshk@tarkett.com

