

THE ACCESS COLLECTION

Affordable beauty engineered to withstand the demands of a busy home. Access is backed by a 15-Year Residential Limited Warranty and a 5-year Light Commercial Limited Warranty.



1. PRODUCT DETAILS

- **Nominal Thickness:** 0.080" (2.0 mm)
- **Wearlayer Thickness:** 6 Mills (0.15 mm)
- **Edge Treatment:** Square
- **Finish:** Durable Urethane

	Planks	Tiles
Size:	6.18" x 48.31" (157 mm x 1227 mm)	12.4" x 24.4" (315 mm x 620 mm)
Sq. Ft. per Carton:	41.47	42.04
Planks per Carton:	20	20
Cartons per Pallet:	66	66
Lbs. per Carton:	32.5 (14.75 kg.)	32.95 (14.95 kg.)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1 **ASTM E648 (Fire):** ≥ 0.45 w/cm²
- 2.2 **ASTM E662 (Smoke):** ≤ 450
- 2.3 **Stain Resistance:** ASTM F925: Passes
- 2.4 **Static Load:** ASTM F970: Passes
- 2.5 **Heat Stability:** ASTM 1514: $\Delta E \leq 2$
- 2.6 **Light Stability:** ASTM F1515: $\Delta E \leq 8$
- 2.7 **FloorScore® Certification:** SCS-EC10.3-2014:SCS-FS-04739

3. INSTALLATION – Refer to Detailed Installation

Instructions at www.tarkettna.com

- Maintain the work area between 65° F and 85° F (18°C - 30°C) for 48 hours before and during and after Installation. Maintain relative humidity between 40% and 70%.
- Cartons shall be stored horizontally on a sturdy base at all times.
- Access™ and ProSheet Plus 3 is an acceptable installation system. (Follow ProSheet Plus 3 Installation Instructions).

4. ADHESIVE

Tarkett QBond-One Adhesive

Releasable - Medium Nap Roller

Permanent - 1/32" x 1/16" x 1/32" trowel

Tarkett 959 Vinyl Tile and Plank Adhesive

Permanent - Porous: 1/16" x 1/16" x 1/16" V-notch or

Non-porous: 1/32" x 1/16" x 1/32" U-notch

Porous/Non-porous: Medium Nap Roller

5. WARRANTY –For complete details, contact Tarkett Technical Services or go to www.tarkettna.com

- 15-YEAR RESIDENTIAL LIMITED WARRANTY
- 5-YEAR LIGHT COMMERCIAL LIMITED WARRANTY

6. MAINTENANCE

- 6.1. Do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- 6.2. Never slide heavy furniture or appliances across the floor. Place sheets of plywood over finished floor when moving furniture and appliances into position.
- 6.3. Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- 6.4. Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- 6.5. Clean floor using Tarkett SureShine® Floor Cleaner or an equivalent pH neutral floor cleaner. Follow manufacturers label instructions for precaution and use.

7. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8297.