

# NuGen™ Glue Down

RIGID CORE

Rigid.  
Flexible.  
Beautiful.

NuGen combines the best of both worlds. Rigid core flooring that is also more flexible, easy to install, and beautiful in any room.

#### Use in Any Room

Waterproof so it's safe to use in kitchens, bathrooms, or laundry rooms.

#### Install Immediately

No acclimation time required. Buy and install immediately after purchase.

#### Rigid Core

Overcomes subfloor imperfections and telegraphing, unlike traditional luxury vinyl tile.

#### Durable

Stands up to kids, pets, high heels and heavy furniture.



WATERPROOF



EASE OF  
MAINTENANCE



DURABILITY



PERMAGRIP  
EASY TO  
INSTALL


MINERAL OAK | LONG GRAIN  
270286004

 **Tarkett**

# NuGen™ Glue Down



**Wessex Rail**  
Ligna  
270286000




**Teak Marado**  
Natural  
270286001




**Sparrow Oak**  
Gray Pearl  
270286002




**Milled Oak**  
Sun Toned  
270286003




**Mineral Oak**  
Long Grain  
270286004




**Chestnut Ridge**  
Furrowed  
270286005




**Pecan Flame**  
Claro  
270286006



**Cottage Plank**  
Bella  
270286007



**Alsace Oak**  
Limed Natural  
270286008



**Driftwood**  
Sand  
270286009

## Specifications

Nominal Thickness	0.138" (3.5 mm)
Wear Layer Thickness	0.012" (0.3 mm)
Finish Edge	Square
Finish	Polyurethane
Material	Phthalate Free, 100% Virgin Material
Reusable Content	100% Reclaimable
Scratch/Scuff/Abrasion Properties	Excellent
Dimensional Stability	ASTM F2199 Passes
Static Load Limit	ASTM F970 Passes
Residual Indentation	ASTM F1914 Passes
Slip Resistance	ASTM D2047 $\geq 0.5$ SCOF
Fire	ASTM E648 $\geq .45$ w/cm <sup>2</sup>
Smoke	ASTM E662 $\leq 450$
Heat Stability	ASTM F1514 $\Delta E \leq 8$
Light Stability	ASTM F1515 $\Delta E \leq 8$
Staining	ASTM F925 Passes
Installation System	Adhesive
FloorScore® Certification	Certified
Size	7.32" x 48.03" (186mm x 1220mm)
Pieces per Carton	12 Planks
Weight per Carton	Planks: 39.47 lbs. (17.9 kgs.)
Area per Carton	29.31 sq. ft. (2.72 m <sup>2</sup> )
Cartons per Pallet	55

## Accessories



### T-Molding

Ensures a smooth transition between flooring at the same height.



### Universal Reducer

Makes an attractive and safe transition between flooring of different heights.



Phthalate Free



## Tarkett North America

30000 Aurora Road  
Solon, OH 44139  
USA: 1-877-TARKETT (1-877-827-5388)  
Canada: 1-877-436-6267

[www.tarkettna.com](http://www.tarkettna.com)

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett dealer to view an actual product sample.

©2020 Tarkett North America 02/2020