

## Resolve

With beautiful design and an affordable price point, Resolve LVT supports your budget goals at every stage—from purchase to installation and maintenance. Easily install these natural-looking wood and stone designs in a variety of artistic layouts. The streamlined collection only includes our best-selling styles, ensuring easy selection and comfortable finished spaces.

## **Planks**



RRW 2505 Ridge Oak



**RRW 2500 Heritage Cherry** 



RRW 2503 Artisian Oak



RRW 2507 Windsor Walnut



RRS 2509 Tuscan Ivory



**RRW 2504 Timberline** 



RRW 2501 White Oak



RRW 2506 Weathered Rosewood



RRW 2502 Nightsgate Tavern



RRS 2509 Riverside

SPECIFICATIONS				
Nominal Thickness	0.098" (2.5 mm)			
Wear Layer Thickness	0.020" (0.5 mm)			
Finish Edge	Square			
Finish	Polyurethane			
Classification	ASTM F1700 Class III Type B			
Dimensional Stability	ASTM F2199 Passes			
Static Load Limit	ASTM F970 Passes			
Residual Indentation	ASTM F1914 Passes			
Slip Resistance	ASTM D2047 ≥ 0.5 SCOF			
Fire	ASTM E648 ≥ 0.45 w/cm <sup>2</sup>			
Smoke	ASTM E662 ≥ 450			
Heat Stability	ASTM F1514 ΔE ≤ 8			
Light Stability	ASTM F1515 ΔE ≤ 8			
Staining	ASTM F925 Passes			
Installation System	Adhesive			
FloorScore® Certification	Certified			
Colors	10			
·	·			

Nominal Thickness	0.098" (2.5 mm)
Wear Layer Thickness	0.020" (0.5 mm)
Finish Edge	Square
Finish	Polyurethane
Classification	ASTM F1700 Class III Type B
Dimensional Stability	ASTM F2199 Passes
Static Load Limit	ASTM F970 Passes
Residual Indentation	ASTM F1914 Passes
Slip Resistance	ASTM D2047 ≥ 0.5 SCOF
Fire	ASTM E648 ≥ 0.45 w/cm <sup>2</sup>
Smoke	ASTM E662 ≥ 450
Heat Stability	ASTM F1514 ΔE ≤ 8
Light Stability	ASTM F1515 ΔE ≤ 8
Staining	ASTM F925 Passes
Installation System	Adhesive
FloorScore® Certification	Certified
Colors	10

Adhesive	Moisture	pН	Foot Traffic	Rolling Loads	Floor Score	Spread Rate Porous	Spread Rate Non-Porous
RollSmart	95% RH 8 lbs. per 1,000 ft2/24 hrs.	7.0- 10.0 pH	Immediately After Installation	Immediately After Installation	Yes	3/8" Nap Paint Roller* 350 - 400 sq. ft.	3/8" Nap Paint Roller* 350 - 400 sq. ft.
959 Vinyl and Tile Adhesive	90% RH 8 lbs. per 1,000 ft2/24 hrs.	7.0- 10.0 pH	24 hrs. After Installation	72 hrs. After Installation	Yes	1/16 x 1/16 x 1/16 V 150 - 175 sq. ft.	1/16 x 1/16 x 1/16 V 250 - 300 sq. ft.
975 Two-Part	Two-Part 85% RH 7.0- 24 hrs. 72 hrs After	Yes	1/16 x 1/16 x 1/16 V 150 - 175 sq. ft.	1/16 x 1/16 x 1/16 V 150 - 175 sq. ft.			
Urethane Adhesive	7 lbs. per 1,000 ft2/24 hrs.	i I Installation I	Yes	1/32 x 1/16 x 1/32 U 150 - 175 sq. ft.	1/32 x 1/16 x 1/32 U 150 - 175 sq. ft.		
						* U.	sed with a paint tray

	PLANKS	TILES	
Size	7.56" x 48.43" (192 mm x 1230 mm)	18.9" x 18.9" (480 mm x 480 mm)	
Sq. Ft. per Carton	40.67 (3.78m²)	39.68 (3.68m²)	
Planks per Carton	16	16	
Lbs. per Carton	40.20 lbs (18.23 kg.)	39.68 lbs (17.96 kg.)	
Cartons per Pallet	50	48	







TARKETTNA.COM 800.899.8916 ©2018 TARKETT 07/18

