

LUXURY VINYL PLANK

Transcend™ Click with FreeSpan™

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Transcend™ luxury vinyl flooring with Click FreeSpan™ locking technology are construction with a durable designed to resist stains, scratches and scuffs.

1.2. Manufacturer:

Tarkett Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139
 Web: www.tarkettna.com
 E-mail: info@johnsonite.com

1.2.1. Construction: Transcend™ Click features FreeSpan™ locking technology for ease of install, durable UV-cured urethane top coat that protects against scuffs, scratches, stains, and wear. Construction includes two layers of fiberglass for dimensional stability.

1.2.2. Styles:

Transcend™ Click

- Nominal Thickness: 0.158" (4 mm)

1.2.3. Packaging

Size	Planks/ Carton	Sq. Ft./ Carton	Cartons/ Pallet
5" x 37" (12.7cm x 94cm)	15	19.35 (1.79 m²/crt)	63
12" x 24" (30.5cm x 61cm)	10	19.27 (1.79 m²/crt)	54
7" x 48" (17.8cm x 121.9cm)	10	24.03 (2.23 m²/crt)	70

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Wear Layer Thickness (ASTM F 410): 20 mil (0.5 mm)
- Size/Tolerance (ASTM F2055): Passes
- Tile Squareness (ASTM F 2055): Passes
- Tile Dimensional Stability (ASTM F 2199): Passes

2.5. Flexibility (ASTM F137): Passes 1 inch mandrel

2.6. Total Thickness (ASTM F 386): 0.158" (4 mm)

2.7. Static Load Limit (ASTM F 970): 250 PSI - Passes

2.8. Resistance to Heat (ASTM F 1514): $\Delta E \leq 8$

2.9. Resistance to Light (ASTM F 1515): $\Delta E \leq 8$

2.10. Slip Resistance (ASTM D 2047): SCOF ≥ 0.5

2.11. Fire Performance (ASTM E648 Radiant Panel): ≥ 0.45 W/cm², Class 1

2.12. Chemical Resistance (ASTM F925): Passes

3. INSTALLATION

- Concrete must not exceed 80% RH in accordance with ASTM F2170 or 5 lbs. MVER in accordance with ASTM F1869.
- See Tarkett Transcend Click installation instructions for complete details.

4. AVAILABILITY

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

Immediate initial maintenance must be implemented after installation.

Refer to the Tarkett flooring Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
 30000 Aurora Road, Solon, Ohio 44139
 (800) 899-8916
 Fax (440) 632-5643
 email: info@johnsonite.com
 www.tarkettna.com