

LUXURY VINYL PLANK

Transcend™ SureSet™

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Transcend™ luxury vinyl floors with SureSet™ are construction with a durable designed to resist stains, scratches and scuffs.

1.2. Manufacturer:

Tarkett Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@johnsonite.com

1.2.1. **Construction:** Transcend™ with SureSet™ technology, features a thin layer of pressure sensitive adhesive applied to a unique sculpted wave designed backing system and a durable UV-cured urethane top coat. Construction includes two layers of fiberglass for dimensional stability.

1.2.2. Styles:

Transcend™ SureSet™

- Nominal Thickness: 0.177" (4.5 mm)

1.2.3. Packaging

Size	Planks/ Carton	Sq. Ft./ Carton	Cartons/ Pallet
12" x 24" (30.5cm x 61cm)	12	24 (2.23 m²/crt)	56
12" x 36" (30.5cm x 91.4cm)	8	24 (2.23 m²/crt)	45
9" x 48" (22.9cm x 121.9cm)	8	24 (2.23 m²/crt)	56
6" x 36" (15.2cm x 91.4cm)	16	24 (2.23 m²/crt)	45

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Wear Layer Thickness (ASTM F 410): 20 mil (0.5 mm)
- Size/Tolerance (ASTM F2055): Passes
- Tile Squareness (ASTM F 2055): Passes
- Tile Dimensional Stability (ASTM F 2199): Passes

2.5. Flexibility (ASTM F137): Passes 1 inch mandrel

2.6. Total Thickness (ASTM F 386): 0.177 in. (4.5 mm)

2.7. Static Load Limit (ASTM F 970): 250 psi - Passes

2.8. Resistance to Heat (ASTM F 1514): $\Delta E \leq 8$

2.9. Resistance to Light (ASTM F 1515): $\Delta E \leq 8$

2.10. Slip Resistance (ASTM D 2047): SCOF ≥ 0.5

2.11. Fire Performance (ASTM E648 Radiant Panel): ≥ 0.45 W/cm², Class 1

2.12. Chemical Resistance (ASTM F925): Passes

2.13. Impact Sound Reduction (ASTM E2179): ΔIIC 12 dB

3. INSTALLATION

- Concrete must not exceed 95% RH in accordance with ASTM F2170 or 9 lbs. MVER in accordance with ASTM F1869.
- See Tarkett Transcend SureSet installation instructions for complete details.

4. AVAILABILITY

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented.

Refer to the Tarkett flooring Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
30000 Aurora Road, Solon, Ohio 44139
(800) 899-8916
Fax (440) 632-5643
email: info@johnsonite.com
www.tarkettna.com