



iQ[®] Granit[™] SD

safety in, static out

iQ Granit SD is a permanently static-dissipative vinyl flooring for use in heavy-traffic laboratories, clean rooms and ESD-sensitive areas in hospitals. It delivers the perfect combination of stable and reliable conductivity alongside the proven durability of the iQ flooring range. It is specially designed to coordinate with the colors of the other products and accessories of the iQ Granit multi-solution family.

 **Tarkett**

iQ GRANIT SD

Explore soft, tonal visuals inspired by the beauty and resilience of natural stone, with a flowing palette that helps us retreat, reflect and recharge.



3096468 SAND
129 SILK WB



3096954 BEIGE
49 BEIGE WB




3096467 WARM SAND
22 PEARL CB



3096474 CLAY
80 FAWN CB




3096436 DARK SAND
09 CLAY WB




3096949 DARK GREY
TG3 IRON MOUNTAIN CG



3096395 LIGHT GREY
TB3 DOVER CG




3096948 GREY
TA5 COLONIAL GREY CG



3096950 BLACK GREY
TA6 BEDROCK CG




3096475 WHITE GREEN
27 MIST WG




3096994 LIGHT GREEN
VM4 GREEN SMOKE



3096980 LIGHT AQUA
TG1 SNOWBOUND W



3096476 LIGHT BLUE
84 BLUE JEANS



3096953 BLACK
40 BLACK B

Weld Rods

Part Number	Collection	Color	Specialty Color Number	Solid Weld Rod	24"x24" Tile Part Number
3096395	iQ Granit SD	Light Grey	395	1287446	314007395
3096948	iQ Granit SD	Grey	948	1287630	314007948
3096949	iQ Granit SD	Dark Grey	949	1287831	314007949
3096950	iQ Granit SD	Black Grey	950	1287842	314007950
3096953	iQ Granit SD	Black	953	1287375	314007953
3096436	iQ Granit SD	Dark Sand	436	1287830	314007436
3096467	iQ Granit SD	Warm Sand	467	1289803	314007467
3096468	iQ Granit SD	Sand	468	1291615	314007468
3096954	iQ Granit SD	Beige	954	1287698	314007954
3096474	iQ Granit SD	Clay	474	1287696	314007474
3096475	iQ Granit SD	White Green	475	1287323	314007475
3096476	iQ Granit SD	Light Blue	476	1287803	314007476
3096980	iQ Granit SD	Light Aqua	980	1287297	314007980
3096994	iQ Granit SD	Light Green	994	1287860	314007994

Specifications

Technical Data	Standards	iQ Granit SD
Classification	ASTM F-1913, ASTM F1700	Homogeneous Vinyl Sheet, Solid Vinyl Tile
Polyurethane Reinforced	ASTM F410	Yes
Total Thickness	ASTM F386	0.080" (2mm)
Static Load Resistance	ASTM F970	250 psi \leq 0.005 inches
Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$
Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$
Residual Indentation	ASTM F1914	Passes
Slip Resistance	ASTM D2047	≥ 0.5 SCOF
Flame Resistance	ASTM E648	Class 1 (≥ 0.45 W/cm ²)
Flame Spread / Smoke (Canada)	CAN/ULC S102.2	FSR 155 / SDC 240
Electrostatic Testing	ASTM F150	10 ⁶ to 10 ⁹ ohms
	ANSI/ESD S7.1	10 ⁶ to 10 ⁹ ohms
	ANSI/ESD STM 97.1	< 10 ⁹ ohms
	ANSI/ESD STM 97.2	< 100 volts
Warranty		20 years
Colors Available		14
Roll	Length	76'
	Width	6' 6" nominal (2 m)
	Weight / yd ² (m ²)	5.79 lbs/yd ²
Tile	Size	24" x 24" (61 cm x 61 cm)
	Pieces per Carton	14 tiles/box
	Area per Carton	56 ft ² (5.2 m ²)
	Weight per Carton	36 lbs./ctn

Please visit tarkett.com for the most updated specifications, and installation, cleaning and maintenance instructions. The weld rods listed are intended to correspond with the denoted flooring colors. Other weld rods can be used for a variety of visual effects.



ORTHO-PHTHALATE
FREE

Tarkett North America

30000 Aurora Road
Solon, Ohio 44139
800.899.8916

tarkett.com

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett dealer to view an actual product sample. All third-party trademarks are the property of their respective owners.