

## **CONTENT DECLARATION**

Trade name: SAFETRED UNIVERSAL

Manufacturer: Tarkett Ltd, Lenham, UK. ME17 2QX

Manufacturing standard: EN 13845

General description: PVC floor coverings with particle based enhanced slip resistance

Date: 24<sup>th</sup> March 2016

Components	Component	CAS number	Weight (%)	Content g/m²
Polymer	Polyvinyl chloride	9001-86-2	13	410 - 420
Plasticizer	HEXAMOL DINCH: 1,2-Cyclohexanedicarboxylic acid, diisononyl ester Effusion DBT: 1,4-Benzenedicarboxylic acid, dibutyl ester	166412-78-8 1962-75-0	3 - 4 2 - 3	97 - 130 65 - 97
Stabilizer blend	Ca/Zn based**, organo-phosphite** epoxidized soyabean oil	8013-07-08	<1	<27
Filler	Mineral fillers	471-34-1 / 546-93-0	<9	<270
Pigments (entire collection)	Titanium dioxide See below* (including lnk**)	13463-67-7	<1 <1	<10 <5
Other components	Calendared PVC backing based on recycled materials and a non- woven glass tissue. PUR reinforcement**		>67 <1	2170 <16
	Silicon carbide: hard angular mineral** Viscosity modifier/surfactants**		<4 <1	125 <1
			100	3230 (nominal)
				2835 - 3560 (manufacturing spec)

In addition, the following pigments according to shade:

\*) Colour Index: Published by: The Society of Dyers and Colourists, Perkin House, 82 Grattan Road, Bradford, Yorkshire, BD1 2LU England.

C.I. Pigment Yellow 42 and 93
C.I. Pigment Red 101 and 144
C.I. Pigment Blue 15:1

\*\*) Exact composition is unknown as they are proprietary blends. We can assist in contacting the manufacturers if more information is required.