

# Aqua Multisafe

## Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Commercial classification	ISO 10874	33 Heavy
Industrial classification	ISO 10874	42 General
Binder content	ISO 10582	Type I
Technical Characteristics	Norm	Tarkett Value
Wear layer thickness	EN ISO 24340	0,55 mm
Total thickness	EN ISO 24346	2 mm
Total weight	EN ISO 23997	3100 g/m <sup>2</sup>
Surface treatment		Top Clean XP
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-096-DoP-2021-05
Reaction to fire	EN ISO 13501-1	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) and/or Cfl-s1 glued over any derivate wood substrate
Static Electrical Propensity	EN 1815	Antistatic ( $\leq 2$ kV)
Thermal resistance	EN ISO 10456	0,02 m <sup>2</sup> •K/W
Slip resistance	EN 13893	Class DS ( $\mu \geq 0,30$ )
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Average measured value: 0,03 mm Required value: $\leq 0.10$ mm
Dimensional stability	EN ISO 23999	Average measured value : $\leq 0.10$ %
Slip resistance	DIN 51130	R10
Slip resistance	DIN 51097	Class C
Castor chair	EN ISO 4918	No damage
Curl resultant to heat	EN ISO 23999	$\leq  8 $ mm
Light fastness	EN ISO 105-B02	$\geq 6$
Chemical resistance	EN ISO 26987	Good resistance
Bacteria Resistance	ISO 846 - Part C	Does not promote growth
Seam Strength Average Value	EN 684	$\geq 240$ N/50mm
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts - Contact Tarkett for more information
Recycled content		33 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5,95 kg CO <sub>2</sub> eq /m <sup>2</sup>
Total VOC Emissions (after 28 days)	EN 16516	Platinum ( $\leq 10$ µg/m <sup>3</sup> )
Formaldehyde emission	EN 717-1	E1
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		10



The above information is subject to modification for the benefit of further improvement (08/10/2024). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.