

Aquarelle Wall HFS

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 233	Vinyl wallcovering in roll form
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	0,92 mm
Total weight	EN ISO 23997	1500 g/m ²
Wear layer thickness	EN ISO 24340	0,12 mm
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 15102	0131-0032-DoP-2020-01
Reaction to fire	EN 13501-1	B-s2,d0 glued on any non-metal A1 or A2-s1,d0 class substrate
Technical Performance	Norm	Tarkett Value
Light fastness	EN ISO 1056B02	≥ 6
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Chemical resistance	EN ISO 26987	Good resistance
Riboflavin Test	ISO 4628-1 - VDI 2083 P17	Class 0 : Excellent
Seam Strength Average Value	ISO 16906	≥ 150 N/50mm
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts - Contact Tarkett for more information
Recycled content		4,5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		4,44 kg CO ₂ eq /m ²
Total VOC Emissions (after 28 days)	ISO 16000-9	Platinum (≤ 10 µg/m ³)
Formaldehyde emission		E1
Dimensions and designs		
Roll		Roll 0,49 x 35m Roll 2 x 35 m
Number of designs available		33



The above information is subject to modification for the benefit of further improvement (11/10/2024). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.