

Eclipse Premium

Datasheet

| Classification | Norm | Tarkett Value |
|--|----------------------|---|
| Product type | ISO 10581 | Homogeneous vinyl floor covering |
| Binder content | ISO 10581 | Type I |
| Commercial classification | ISO 10874 | 34 Very Heavy |
| Industrial classification | ISO 10874 | 43 Heavy |
| Technical Characteristics | Norm | Tarkett Value |
| Surface treatment | | Premium Pro |
| Total thickness | ISO 24346 | 2 mm |
| Wear layer thickness | ISO 24340 | 2 mm |
| Total weight | ISO 23997 | 2900 g/m ² |
| Performance for CE Marking | Norm | Tarkett Value |
| Declaration of Performance # | EN 14041 | 0019-0020-DoP-2013-07 |
| Reaction to fire | EN 13501-1 | Bfl-s1 |
| Reaction to fire | EN ISO 9239-1 | ≥ 8 kW/m ² |
| Reaction to fire - EN ISO 11925-2 | EN ISO 11925-2 | Pass |
| Static Electrical Propensity | EN 1815 | Antistatic (≤ 2 kV) |
| Thermal resistance | EN 12667 | ~0,010 m ² ·K/W |
| Slip resistance (EN 13893) | EN 13893 | Class DS (μ ≥ 0,30) |
| Technical Performance | Norm | Tarkett Value |
| Residual indentation | EN ISO 24343-1 | ≤ 0,10 mm Best measured value: 0,03 mm |
| Slip resistance | DIN 51130 | R9/R10 - On demand |
| Slip Resistance (EN 16165 Annex C) | BS 7976-2 | Low risk of slip |
| Pendulum | EN 16165 Annex C | ≥ 36 |
| Clean room | ISO 14644-1 | ISO class 4 |
| Castor chair | ISO 4918 | Suitable |
| Light fastness | ISO 105-B02 | ≥ 7 |
| Dimensional stability | EN ISO 23999 | ≤ 0.40 % |
| Ease of Decontamination | ISO 8690 – DIN 25415 | Excellent |
| Chemical resistance | ISO 26987 | Excellent Resistance |
| Bacteria Resistance | ISO 846 Part C | Does not promote growth |
| Underfloor heating | | Suitable (subfloor temperature maximum 27°C) |
| Wetroom approval | EN 13553 Annex A | Watertight |
| Seam Strength Average Value | EN 684 | ≥ 400 N/50mm |
| Sustainability performances | Norm | Tarkett Value |
| Recyclability through ReStart® | | Offcuts / Post-use - Contact Tarkett for more information |
| Recycled content | | 25,5 % |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) | | 3,78 kg CO ₂ eq /m ² |
| Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario) | | 4,81 kg CO ₂ eq /m ² |
| Total VOC Emissions (after 28 days) | EN 16516 | Platinum (≤ 10 µg/m ³) |
| Formaldehyde emission | | E1 |
| Dimensions and designs | | |
| Roll | | Roll 2 x 23 m |
| Number of designs available | | 56 |



The above information is subject to modification for the benefit of further improvement (02/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.