

Etrusco xf²™ Bfl 2,5 mm

Datasheet

Classification	Norm	Tarkett Value	Requirement
Product type	ISO 24011	Plain and decorative linoleum (ISO 24011)	
Commercial classification	ISO 10874	34 Very Heavy	
Industrial classification	ISO 10874	43 Heavy	
Technical Characteristics	Norm	Tarkett Value	Requirement
Country of origin		Italy	
Surface treatment		xf2	
Total thickness	ISO 24346	2.5 mm	
Total weight	ISO 23997	3.2 kg/m ²	
Installation method		Glue-Down	
Format Type		Roll	
Performance for CE Marking	Norm	Tarkett Value	Requirement
CE Marking		EN 14041	
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)	
Declaration of Performance #		0200-0014-DoP-2013-07	
Thermal resistance (m ² ·K/W)	ISO 10456	0,015 m ² ·K/W	
Technical Performance	Norm	Tarkett Value	Requirement
Impact sound reduction - ΔL_w	EN ISO 717-2	5 dB	
Castor chair effect	ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)	
Underfloor heating		YES_27	
Colour fastness to light	ISO 105-B02	≥ 6	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value	Requirement
Phthalate - free	CEN ISO/TS 16181	Yes	
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum (≤ 10 μg / m ³)	
Dimensions and designs			
Roll		Roll 2 x ≤ 16 m	
Number of designs available		16	



The above information is subject to modification for the benefit of further improvement (14/02/2022). Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com