

ICONIK 260Tex

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering
Domestic classification	EN ISO 10874	22 / 22+ Domestic general medium / Domestic general
Binder content	ISO 11638	Type I
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2,60 mm
Wear layer thickness	ISO 24340	0,20 mm
Total weight	ISO 23997	1530 g/m ²
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0007-0085-DOP-2024-10
Reaction to fire	EN 13501-1	Cfl-s1
Slip resistance (EN 13893)	EN 13893	Class DS ($\mu \geq 0,30$)
Slip resistance	DIN 51130	R10
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	ISO 10456	0,040 m ² ·K/W
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	$\leq 0,35$ mm
Impact sound reduction - ΔL_w	EN ISO 717-2	18 dB
Light fastness	ISO 105-B02	≥ 6
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Dimensional stability	EN ISO 23999	$\leq 0,15$ %
Curl resultant to heat	ISO 23999	$\leq 8 $ mm
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Recycled Content (up to)		32 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		3,63 kg CO ₂ eq / m ²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		2,41 kg CO ₂ eq / m ²
Total VOC Emissions (after 28 days)	EN 16516	Gold (≤ 100 $\mu\text{g} / \text{m}^3$)
BREEAM rating		A+
Formaldehyde emission		E1
Dimensions and designs		
Roll		Roll 2 x 25 m Roll 3 x 25 m Roll 4 x 25 m
Number of designs available		31



The above information is subject to modification for the benefit of further improvement (05/03/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.