

# iD Comfort Acoustic

## Datasheet

| Classification   | Norm  | Tarkett Value  |
|--|---|--|
| Product type   | EN ISO 11638  | Heterogeneous poly(vinyl chloride) floor coverings           |
| Domestic classification  | EN ISO 10874  | 23 Heavy   |
| Commercial classification  | EN ISO 10874  | 32 General   |
| Commercial warranty (in years)                                     |   | 10 years   |
| Technical Characteristics  | Norm  | Tarkett Value  |
| Total thickness  | EN ISO 24346  | 3,15 mm  |
| Wear layer thickness   | EN ISO 24340  | 0,35 mm  |
| Total weight   | EN ISO 23997  | 3040 g/m <sup>2</sup>  |
| Binder content   | EN ISO 10582  | Type I   |
| Bevelled edges   |   | No bevel   |
| Installation method  |   | Loose-Lay  |
| Performance for CE Marking   | Norm  | Tarkett Value  |
| Declaration of Performance #                                       | EN 14041  | 0120-106-DoP-2024-07   |
| Technical Performance  | Norm  | Tarkett Value  |
| Dimensional stability  | EN ISO 23999  | ≤ 0,10 %   |
| Curl resultant to heat   | EN ISO 23999  | [-1;1]   |
| Reaction to fire   | EN 13501-1  | Cfl-s1   |
| Residual indentation   | EN ISO 24343-1  | Required value: ≤ 0,20 mm<br>Average measured value: 0,15 mm |
| Furniture leg  | EN ISO 16581  | No damage  |
| Castor chair   | EN ISO 4918   | No damage  |
| Impact sound reduction - ΔLw                                       | EN ISO 717-2  | 19 dB  |
| Reduction of in-room impact noise                                  | NF S31-074  | Class A (≤ 65 dB)  |
| Thermal resistance   | EN ISO 10456  | 0,04 m <sup>2</sup> ·K/W                                     |
| Light fastness   | EN ISO 105-B02  | ≥ 6  |
| Chemical resistance  | EN ISO 26987  | Not affected   |
| Slip resistance  | DIN 51130   | R10  |
| Slip resistance (EN 13893)   | EN 13893  | Class DS (μ ≥ 0,30)  |
| Static Electrical Propensity                                       | EN 1815   | Antistatic (≤ 2 kV)  |
| Underfloor heating   |   | Suitable (subfloor temperature maximum 27°C)                 |
| Sustainability performances  | Norm  | Tarkett Value  |
| Recyclability through ReStart®                                     |   | Offcuts / Post-use - Contact Tarkett for more information    |
| Recycled content   | ISO 14021   | 33 %   |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)               |   | 4,90 kg CO <sub>2</sub> eq /m <sup>2</sup>                   |
| Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario) |   | 5,48 kg CO <sub>2</sub> eq /m <sup>2</sup>                   |
| Total VOC Emissions (after 28 days)                                | EN 16516  | Platinum (≤ 10 μg/m <sup>3</sup> )                           |
| Dimensions and designs   |   |  |
| Plank  | Plank 1200x200mm - 18 planks=4,32 m <sup>2</sup> /box - 44 boxes/pallet |  |
| Tile   | Tile 50x50mm - 18 tiles=4,5 m <sup>2</sup> /box - 44 boxes/pallet       |  |
| Number of designs available  | 25  |  |



The above information is subject to modification for the benefit of further improvement (07/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.