

# iD Evolution

## Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 19322	Floor coverings based on thermoplastic polymers
Commercial classification	EN ISO 10874	34 Very Heavy
Industrial classification	EN ISO 10874	43 Heavy
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	2,50 mm
Total weight	ISO 23997	4100 g/m <sup>2</sup>
Surface treatment		PU Mat
Bevelled edges		4 sides micro bevels
Installation method		Glue-Down
Commercial warranty (in years)		10 years
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0132-0092-DoP-2023-09
Technical Performance	Norm	Tarkett Value
Dimensional stability	ISO 23999 - B method	≤ 0,15 %
Curl resultant to heat	ISO 23999 - B method	≤  2  mm
Reaction to fire	EN 13501	Cfl-s1
Residual indentation	ISO 24343-1	≤ 0,10 mm
Castor chair	EN ISO 4918	No damage after 25000 cycles
Furniture leg	ISO 16581	No damage
Furniture leg	ISO 16581	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	2 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Slip resistance	EN 16165	R10
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		11,30 kg CO <sub>2</sub> eq /m <sup>2</sup>
Total VOC Emissions (after 28 days)	ISO 16000	Platinum (≤ 10 μg/m <sup>3</sup> )
Product Health Declaration		Platinum
REACH		Yes
Dimensions and designs		
Plank	Plank 183 x 1219 mm - 20 planks=4,49 m <sup>2</sup> /box - 50 boxes/pallet	
Tile	Tile 305 x 610 mm - 24 tiles=4,46 m <sup>2</sup> /box - 48 boxes/pallet	
Number of designs available	10	



The above information is subject to modification for the benefit of further improvement (19/03/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.