

iD Inspiration Marine

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 19322	Floor coverings based on thermoplastic polymers
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	2,50 mm
Wear layer thickness	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	4100 g/m ²
Surface treatment		PUR
Bevelled edges		No bevel
Installation method		Glue-Down
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	≤ 0,15 %
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Castor chair	EN ISO 4918	No damage
Thermal resistance	EN ISO 10456	0,02 m ² •K/W
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Slip resistance	DIN 51130	R10
Sustainability performances	Norm	Tarkett Value
Recycled content	ISO 14021	15 %
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m ³)
Dimensions and designs		
Plank	Plank 152 x 1219 mm - 18 planks=3,34 m ² /box - 65 boxes/pallet Plank 183 x 1219 mm - 15 planks=3,37 m ² /box - 64 boxes/pallet	
Tile	Tile 457 x 914 mm - 8 tiles=3,34 m ² /box - 64 boxes/pallet	
Number of designs available	16	



The above information is subject to modification for the benefit of further improvement (03/04/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.