


iD Naturals Loose-Lay 55

Datasheet

| Classification | Norm | Tarkett Value |
|-------------------------------------|--|---|
| Product type | EN ISO 10582 | Heterogeneous poly(vinyl chloride) floor coverings |
| Domestic classification | EN ISO 10874 | 23 Heavy |
| Commercial classification | EN ISO 10874 | 33 Heavy |
| Industrial classification | EN ISO 10874 | 42 General |
| Commercial warranty (in years) | | 10 years |
| Technical Characteristics | Norm | Tarkett Value |
| Total thickness | EN ISO 24346 | 4,50 mm |
| Wear layer thickness | EN ISO 24340 | 0,55 mm |
| Total weight | EN ISO 23997 | 7800 g/m ² |
| Binder content | EN ISO 10582 | Type I |
| Surface treatment | | TEKTANIUM® |
| Bevelled edges | | No bevel 4 sides |
| Installation method | | Loose-Lay |
| Performance for CE Marking | Norm | Tarkett Value |
| Declaration of Performance # | EN 14041 | 0197-0017-DoP-2026-01 |
| Technical Performance | Norm | Tarkett Value |
| Dimensional stability | EN ISO 23999 | Average measured value : ≤ 0.10 % |
| Curl resultant to heat | EN ISO 23999 | ≤ 1 mm |
| Reaction to fire | EN 13501-1 | Bfl-s1 |
| Residual indentation | EN ISO 24343-1 | ≤ 0,10 mm |
| Furniture leg | EN ISO 16581 | No damage |
| Castor chair | EN ISO 4918 | No damage |
| Impact sound reduction - ΔLw | EN ISO 717-2 | 6 dB |
| Reduction of in-room impact noise | NF S31-074 | Class C (≤ 85 dB) |
| Thermal resistance | EN ISO 10456 | 0,04 m ² ·K/W |
| Light fastness | EN ISO 105-B02 | ≥ 6 |
| Chemical resistance | EN ISO 26987 | Good resistance |
| Slip resistance | EN 16165 Annex B | R10 |
| Slip resistance (EN 13893) | EN 13893 | Class DS (μ ≥ 0,30) |
| Static Electrical Propensity | EN 1815 | Antistatic (≤ 2 kV) |
| Underfloor heating | | Suitable (subfloor temperature maximum 27°C) |
| Sustainability performances | Norm | Tarkett Value |
| Recyclability through ReStart® | | Offcuts / Post-use - Contact Tarkett for more information |
| Recycled content | ISO 14021 | 20 % |
| Total VOC Emissions (after 28 days) | EN 16516 | Platinum (≤ 10 μg/m ³) |
| REACH | | Yes |
| Dimensions and designs | | |
| Tile | Tile 660x660mm - 5 tiles=2,18 m ² /box - 42 boxes/pallet Tile 997 x 497mm - 5 tiles=2,48 m ² /box - 42 boxes/pallet | |
| Number of designs available | 5 | |



The above information is subject to modification for the benefit of further improvement (01/06/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.