

iD Tilt HIT

Datasheet

Classification	Norm	Tarkett Value	Requirement
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings (ISO 10582)	
Commercial classification	EN ISO 10874	34 Very Heavy	
Industrial classification	EN ISO 10874	43 Heavy	
Technical Characteristics	Norm	Tarkett Value	Requirement
Total thickness	EN ISO 24346	6 mm	
Wear layer thickness	EN ISO 24340	2.70 mm	
Total weight	EN ISO 23997	10000 g/m ²	
Binder content	EN ISO 10582	TYPE2	
Surface treatment		Top Clean XP	
Bevelled edges		No bevel	
Installation method		Interlocking	
Performance for CE Marking	Norm	Tarkett Value	Requirement
Declaration of Performance #	EN 14041	0197-0015-DoP-2021-10	
Technical Performance	Norm	Tarkett Value	Requirement
Dimensional stability	EN ISO 23999	AMV_LE010 ≤ 0,15 %	
Curl resultant to heat	EN ISO 23999	≤ 1 mm	
Reaction to fire	EN 13501-1	Bfl-s1	
Residual indentation	EN ISO 24343-1	≤ 0.10 mm	
Furniture leg effect	EN ISO 16581	No damage	
Castor chair effect	EN ISO 4918	No damage	
Impact sound reduction - ΔLw	EN ISO 717-2	6 dB	
Drum sound class	NF S31-074	Class C (≤ 85 dB)	
Colour fastness to light	EN ISO 105-B02	≥ 6	
Chemical resistance ISO	EN ISO 26987	Not affected	
Slip resistance	DIN 51130	R10	
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)	μ ≥ 0,30
Peeling Resistance	EN ISO 24345	≥ 100 N/50mm	
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value	Requirement
ReStart® Ready		Yes	
Recycled Content UP TO		15 %	
Phthalate - free		Yes	
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum (≤ 10 μg / m ³)	
Made In		Europe	
Dimensions and designs			
Tile		Tile 645x645mm - 4 Tile=1.59 m ² /box - 48 box/pallet	
Number of designs available		3	



The above information is subject to modification for the benefit of further improvement (25/04/2023). Tarkett reserves the right to maned this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com