

iQ Eminent

Datasheet

Classification	Norm	Tarkett Value	Requirement
Product type	ISO 10581	Homogeneous poly(vinyl chloride) floor covering (ISO 10581)	
Commercial classification	ISO 10874	34 Very Heavy	
Industrial classification	ISO 10874	43 Heavy	
Technical Characteristics	Norm	Tarkett Value	Requirement
Country of origin		Sweden	
Surface treatment		New iQ PUR	
Total thickness	ISO 24346	2 mm	
Wear layer thickness	ISO 24340	2 mm	
Total weight	ISO 23997	2750 g/m ²	
Binder content	ISO 10581	Type I	
Installation method		Glue-Down	
Format Type		Roll Tile	
Items per box		14	
Surface per box		5.2 m ²	
Gross weight		3.742 kg 3.608 kg	
Performance for CE Marking	Norm	Tarkett Value	Requirement
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)	
Declaration of Performance #	EN 14041	0019-0008-DoP-2013-07	
Slip resistance		R9	
Slip resistance	EN 13893	Class DS ($\mu \geq 0,30$)	
Thermal resistance (m ² •K/W)	EN 12667 / ISO 10456	~0,010 m ² •K/W	
Technical Performance	Norm	Tarkett Value	Requirement
Castor chair effect	ISO 4918	Suitable	Suitable
Clean room	ISO 14644-1	ISO class 4	
Fungi and bacteria resistance	ISO 846 - Part C	Does not promote growth	
Chemical resistance ISO	ISO 26987	Excellent Resistance	
Underfloor heating		YES_27	
Colour fastness to light	ISO 105-B02	≥ 7	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value	Requirement
Recycled content		25.5 %	
ReStart® Ready		Yes	
Phthalate - free		Yes	
Dimensions and designs			
Roll		Roll 2x23m	
Tile		Tile 610 x 610 mm - 14 Tile=5.2 m ² /box - 40 box/pallet	
Number of designs available		26	



The above information is subject to modification for the benefit of further improvement (05/05/2022). Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com