

iQ ONE

Datasheet

Classification	Norm	Tarkett Value
Product type		Floor coverings based upon synthetic thermoplastic polymers (EN 14565)
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	Norm	Tarkett Value
Country of origin		Sweden
Surface treatment		New iQ PUR
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	2.8 kg/m ²
Installation method		Glue-Down
Format Type		Roll
Performance for CE Marking	Norm	Tarkett Value
CE Marking		EN 14041
Formaldehyde emission class	EN 717-1	E1
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Content of Pentachlorophenol		< 5 ppm
Declaration of Performance #		0019-0056-DoP-2015-11
Reaction to fire on fibreceement substrate	EN 13501-1	Bfl-s1
Technical Performance	Norm	Tarkett Value
Castor chair effect	ISO 4918	Suitable
Chemical resistance ISO	ISO 26987	Excellent Resistance
Underfloor heating		YES_27
Colour fastness to light	ISO 105-B02	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
ReStart® Ready		Yes
Phthalate - free		Yes
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Gold (≤ 100 $\mu\text{g} / \text{m}^3$)
Dimensions and designs		
Roll		Roll 2x23m
Number of designs available		10



The above information is subject to modification for the benefit of further improvement (14/12/2023). Tarkett reserves the right to maned this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com