

LinoMarine

Datasheet

Classification	Norm	Tarkett Value
Commercial classification	EN ISO 10874	34 Very Heavy
Technical Characteristics	Norm	Tarkett Value
Surface treatment		xf ² [™]
Total thickness	ISO 24346	2,50 mm
Total weight	ISO 23997	3200 g/m ²
Flexibility	ISO 24344 Method A	≤ 30 mm ø
Performance for CE Marking	Norm	Tarkett Value
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	≤ 0,15 mm
Castor chair	EN ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)
Chemical resistance	ISO 26987	Resistant to dilute acids, oils, fats, current solvents and alkalis
Light fastness	ISO 105-B02	≥ 6
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		-1,70 kg CO ₂ eq / m ²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		-1,92 kg CO ₂ eq / m ²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m ³)
Dimensions and designs		
Roll		Roll 2 x ≤16m
Number of designs available		50



The above information is subject to modification for the benefit of further improvement (06/03/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.