

LinoWall xf² (2mm)

Datasheet

| Classification | Norm | Tarkett Value |
|---|---|---|
| Product type | ISO 24011 (EN 548) | Approved linoleum for walls application |
| Technical Characteristics | Norm | Tarkett Value |
| Total thickness | EN ISO 24346 | 2 mm |
| Total weight | EN ISO 23997 | 2900 g/m ² |
| Surface treatment | | xf ² [™] |
| Installation method | | Glue-Down |
| Performance for CE Marking | Norm | Tarkett Value |
| Declaration of Performance # | EN 15102 | 0200 0045 DoP 2013 07 |
| Reaction to fire | EN 13501-1 | B-s ₂ d ₀ |
| Fire Effluent Toxicity | ISO 5659-2 (evaluation according to EN 45545-2 annex C) | CITg (4min) =0,06 and CITg (8min)=0,09 testing with irradiance of 50KW/m ² without pilot flame |
| Static Electrical Propensity | EN 1815 | Antistatic (≤ 2 kV) |
| Thermal conductivity (W/m K) | EN ISO 10456 | 0.11 |
| Technical Performance | Norm | Tarkett Value |
| Impact Resistance | EN 259-2 | Resistant to impacts - No visible burst nor crack |
| Chemical resistance | ISO 26987 - EN 423 | Resistant to dilute acids, oils, fats, current solvents and alkalis |
| Light fastness | ISO 105-B02 | ≥ 6 |
| Odor Test Requirement of Emission Class M1 | EN ISO 16000-28 i.A, VDI 4302 | Meets Requirement |
| Spongeability, washability, lyability, brushability | EN 12956 / EN 233 | Extra washable |
| Determination of antibacterial activity | ISO 22196 | Naturally antibacterial (Bacteria mix - Ecoli and MRSA) |
| Sustainability performances | Norm | Tarkett Value |
| Recyclability through ReStart® | | Offcuts / Post-use - Contact Tarkett for more information |
| Total VOC Emissions (after 28 days) | EN 16516 | Platinum (≤ 10 µg/m ³) |
| Dimensions and designs | | |
| Roll | | Roll 2 x ≤16m |
| Number of designs available | | 10 |



The above information is subject to modification for the benefit of further improvement (20/02/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.