

ProtectWall CR (CLEAN ROOMS)

Datasheet

Classification	Norm	Tarkett Value
Product type		Heavy Duty Wall Covering (EN 259-1)
Technical Characteristics	Norm	Tarkett Value
Country of origin		Luxembourg
Surface treatment		Top Clean XP
Total thickness		1.5 mm
Wear layer thickness		0.15 mm
Total weight		2.4 kg/m ²
Installation method		Glue-Down
NCS color code		S 2002-Y50R S 1005-Y10R
Format Type		Roll
Performance for CE Marking	Norm	Tarkett Value
CE Marking		EN 15102
Declaration of Performance #		0132-0065-DoP-2022-01
Technical Performance	Norm	Tarkett Value
Chemical resistance ISO		Not affected
Colour fastness to light	ISO 105-B02	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
ReStart® Ready		Yes
Phthalate - free		Yes
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum (≤ 10 µg / m ³)
Dimensions and designs		
Roll		Roll 2x20m
Number of designs available		2



The above information is subject to modification for the benefit of further improvement (17/05/2022). Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com