

SAFETRED SPECTRUM

Datasheet

Classification	Norm	Tarkett Value
Product type		Polyvinyl chloride floor coverings with particle based enhanced slip resistance (EN 13845)
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	Norm	Tarkett Value
Country of origin		United Kingdom
Surface treatment		Safety Clean XP
Total thickness	ISO 24346	2 mm
Total weight	ISO 23997	3.41 kg/m ²
Binder content	ISO 10582	Type I
Installation method		Glue-Down
Format Type		Roll
Items per box		Tile
		16
Performance for CE Marking	Norm	Tarkett Value
CE Marking		EN 14041
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Declaration of Performance #		0170-0003-DoP-2020-10
Slip resistance		R10
Slip resistance		Class DS ($\mu \geq 0,30$)
Thermal resistance (m ² •K/W)	ISO 10456	0,010 m ² •K/W
Technical Performance	Norm	Tarkett Value
Furniture leg effect	EN 424	No damage
Impact sound reduction - ΔL_w	EN ISO 717-2	4 dB
Castor chair effect	ISO 4918	No damage
Chemical resistance ISO	ISO 26987	Good resistance
Underfloor heating		YES_27
Colour fastness to light	ISO 105-B02	≥ 7
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recycled content		42 %
ReStart® Ready		Yes
Phthalate - free		Yes
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum ($\leq 10 \mu\text{g} / \text{m}^3$)
Dimensions and designs		
Roll		Roll 2x20m
Tile		Tile 500x500mm - 16 Tile=4 m ² /box - 48 box/pallet
Number of designs available		16



The above information is subject to modification for the benefit of further improvement (24/02/2022). Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com