

Starfloor Click Solid 55 & 55 Plus

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	33 Heavy
Residential warranty (in years)		20 years
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	5 mm
Wear layer thickness	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	8850 g/m ²
Binder content	EN ISO 10582	Type I
Surface treatment		TopCoat
Embossing in Register		Yes
Bevelled edges		4 sides
Installation method		Click
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0197-0010-DoP-2021-02
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	≤ 0,15 % Average measured value : ≤ 0.10 %
Curl resultant to heat	EN ISO 23999	≤ 111 mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Furniture leg	EN ISO 16581	No damage
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	5 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Thermal resistance	EN ISO 10456	0,05 m ² ·K/W
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Slip resistance	DIN 51130	R9 R10
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Peeling Resistance	EN ISO 24345	≥ 50N/50mm
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Recycled content	ISO 14021	35 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		13,38 kg CO ₂ eq /m ²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		6,79 kg CO ₂ eq /m ²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m ³)
Dimensions and designs		
Plank	Plank 1211 x 190,5mm - 7 planks=1,61 m ² /box - 56 boxes/pallet Plank 240 x 1491 mm - 4 planks=1,43 m ² /box - 63 boxes/pallet	
Tile	Tile 323,8 x 601 mm - 8 tiles=1,56 m ² /box - 60 boxes/pallet Tile 500 x 1000 mm - 3 tiles=1,46 m ² /box - 62 boxes/pallet	
Number of designs available	20	

Embossing in register : available only for Highland Oak and Delicate Oak

Slip Resistance R10 : only for Highland Oak and Delicate Oak



The above information is subject to modification for the benefit of further improvement (07/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.