

# Starfloor Click Ultimate 55

## Datasheet

| Classification                    | Norm   | Tarkett Value                                      |
|-----------------------------------|--|--|
| Product type                      | EN ISO 10582   | Heterogeneous poly(vinyl chloride) floor coverings |
| Domestic classification           | EN ISO 10874   | 23 Heavy   |
| Commercial classification         | EN ISO 10874   | 33 Heavy   |
| Technical Characteristics         | Norm   | Tarkett Value                                      |
| Total thickness                   | EN ISO 24346   | 6,50 mm  |
| Wear layer thickness              | EN ISO 24340   | 0,55 mm  |
| Total weight                      | EN ISO 23997   | 11300 g/m <sup>2</sup>                             |
| Binder content                    | EN ISO 10582   | Type I   |
| Surface treatment                 |  | PUR Ultimate                                       |
| Embossing in Register             |  | Yes  |
| Bevelled edges                    |  | 4 sides micro bevels                               |
| Installation method               |  | Click  |
| Performance for CE Marking        | Norm   | Tarkett Value                                      |
| Declaration of Performance #      | EN 14041   | 0132-0070-DoP-2018-12                              |
| Technical Performance             | Norm   | Tarkett Value                                      |
| Dimensional stability             | EN ISO 23999   | ≤ 0,10 %   |
| Curl resultant to heat            | EN ISO 23999   | ≤  1  mm   |
| Reaction to fire                  | EN 13501-1   | Bfl-s1   |
| Residual indentation              | EN ISO 24343-1   | ≤ 0,05 mm  |
| Furniture leg                     | EN ISO 16581   | No damage  |
| Castor chair                      | EN ISO 4918  | No damage  |
| Impact sound reduction - ΔLw      | EN ISO 717-2   | 19 dB  |
| Reduction of in-room impact noise | NF 531-074   | Class C (≤ 85 dB)                                  |
| Thermal resistance                | EN ISO 10456   | 0,05 m <sup>2</sup> •K/W                           |
| Colour fastness to light          | EN ISO 105-B02   | ≥ 6  |
| Chemical resistance               | EN ISO 26987   | Good resistance                                    |
| Slip resistance                   | DIN 51130  | R9<br>R10  |
| Slip resistance                   | EN 13893   | Class DS (μ ≥ 0,30)                                |
| Peeling Resistance                | EN ISO 24345   | ≥ 50N/50mm   |
| Static Electrical Propensity      | EN 1815  | Antistatic (≤ 2 kV)                                |
| Underfloor heating                |  | Suitable (subfloor temperature maximum 27°C)       |
| Sustainability performances       | Norm   | Tarkett Value                                      |
| Recyclability through ReStart®    |  | Recyclable   |
| Total VOC Emissions               | EN 16516   | Gold (≤ 100 μg / m <sup>3</sup> )                  |
| Dimensions and designs            |  |  |
| Plank                             | Plank 176 x 1213 mm - 6 planks=1,281 m <sup>2</sup> /box - 60 boxes/pallet |  |
| Tile                              | Tile 300 x 600 mm - 7 tiles=1,26 m <sup>2</sup> /box - 60 boxes/pallet     |  |
| Number of designs available       | 21   |  |

Embossing in register : available for Highland Oak, Delicate Oak, Weathered Oak, Bleached Oak, Stylish Oak

Slip resistance : R9 for Stylish Oak, Timeless Concrete, Old Stone



The above information is subject to modification for the benefit of further improvement (03/10/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.