

STYLE ELLE SILENCIO xf^2 ™ 18 dB

Datasheet

Classification	Norm	Tarkett Value
Product type		Plain and decorative linoleum on a foam backing (EN 686)
Commercial classification	ISO 10874	33 Heavy
Industrial classification	ISO 10874	41 Moderate
Technical Characteristics	Norm	Tarkett Value
Country of origin		Italy
Surface treatment		xf2
Total thickness	ISO 24346	3.8 mm
Light Reflectance Value (LRV) %		22
Total weight	ISO 23997	3.45 kg/m²
Installation method		Glue-Down
NCS color code		S 5005-Y20R
Format Type		Roll
Performance for CE Marking	Norm	Tarkett Value
CE Marking		EN 14041
Formaldehyde emission	EN 717-1	Formaldehyde free
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Declaration of Performance #		0200 0027 DoP 2013 07
Thermal resistance (m²·K/W)	ISO 10456	0,042 m²·K/W
Technical Performance	Norm	Tarkett Value
Impact sound reduction - ΔL_w	EN ISO 717-2	19 dB
Castor chair effect	ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)
Underfloor heating		YES_27
Colour fastness to light	ISO 105-B02	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Phthalate - free		Yes
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum ($\leq 10 \mu\text{g} / \text{m}^3$)
Dimensions and designs		
Roll		Roll 2 x $\leq 32\text{m}$
Number of designs available		1



The above information is subject to modification for the benefit of further improvement (14/02/2022). Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com