

Surface Wall

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 259-1	Heavy Duty Wall Covering
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	2 mm
Total weight	EN ISO 23997	3400 g/m ²
Wear layer thickness	EN ISO 24340	2 mm
Surface treatment		PU SHIELD
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 15102	0019-0065-DoP-2019-07
Reaction to fire	EN 13501-1	B-s2,d0
Technical Performance	Norm	Tarkett Value
Light fastness	ISO 105-B02	≥ 7
Chemical resistance	ISO 26987	Excellent Resistance
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Recycled content		25,5 %
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m ³)
Formaldehyde emission		E1
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		7



The above information is subject to modification for the benefit of further improvement (04/05/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.