

# Tapiflex Excellence Genius 70

## Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 11638	Polyvinyl chloride floor coverings with foam layer
Binder content	EN ISO 11638	Type I
Commercial classification	EN ISO 10874	34 Very Heavy
Industrial classification	EN ISO 10874	42 General
Wear group	EN 651	T
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	3,50 mm
Wear layer thickness	ISO 24340	0,70 mm
Total weight	ISO 23997	3680 g/m <sup>2</sup>
Surface treatment		TEKTANIUM®
Installation method		Loose-Lay
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-093-DOP-2019-12
Reaction to fire	EN ISO 13501-1	Cfl-s1 loose-lay on an A1fl and / or A2fl substrate (concrete)Cfl-s1 loose-lay on a wooden sub-floor
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN ISO 10456	0,04 m <sup>2</sup> ·K/W
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,20 mm Average measured value: 0,12 mm
Dimensional stability	EN ISO 23999	≤ 0.40 % Average measured value : ≤ 0.10 %
Impact sound reduction - ΔLw	EN ISO 717/2	19 dB
Reduction of in-room impact noise	NF S31-074	Class A (≤ 65 dB)
Slip resistance	EN 16165 national Annex NB.2	R10
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Curl resultant to heat	EN ISO 23999	≤  3  mm
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Recycled content		29 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5,22 kg CO <sub>2</sub> eq /m <sup>2</sup>
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		4,75 kg CO <sub>2</sub> eq /m <sup>2</sup>
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m <sup>3</sup> )
Formaldehyde emission values		< 10
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		25

Slip resistance : R10 only for Long Modern Oak, OakTree, Scandinavian Oak and Serene Oak designs



The above information is subject to modification for the benefit of further improvement (19/03/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.