


Tapiflex Stairs

Datasheet

	Norm	Tapiflex Stairs (glue-down)	Tapiflex Stairs (self-adhesive)
Classification			
Product type	EN ISO 11638	Polyvinyl chloride floor coverings with foam layer	
Commercial classification	ISO 10874	34 Very Heavy	
Industrial classification	ISO 10874	42 General	43 Heavy
Technical Characteristics			
Total thickness	ISO 24346	3,30 mm	
Wear layer thickness	ISO 24340	0,85 mm	
Total weight	ISO 23997	3250 g/m ²	
Surface treatment		Top Clean XP	
Installation method		Glue-Down	Self-Adhesive
Performance for CE Marking			
Declaration of Performance #	EN 14041	0120-025-DoP-2024-02	0120-069-DoP-2024-02
Reaction to fire	EN ISO 13501-1	Bfl-s1 glued over any A2fl or A1fl substrate (concrete) and/or Bfl-s1 glued over any derivate wood substrate	
Reaction to fire on fibrecement substrate	EN ISO 13501-1	Cfl-s1	
Reaction to fire on woodchip substrate	EN ISO 13501-1	Cfl-s1	
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)	
Thermal resistance	EN ISO 10456	0,040 m ² •K/W	
Slip resistance	EN 13893	Class DS ($\mu \geq 0,30$)	
Technical Performance			
Residual indentation	EN ISO 24343-1	Average measured value: 0,17 mm Required value: $\leq 0,20$ mm	
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 %	
Impact sound reduction - ΔL_w	EN ISO 717/2	18 dB	
Reduction of in-room impact noise	NF S31-074	Class A (≤ 65 dB)	
Slip resistance	DIN 51130	R10	
Furniture leg	EN ISO 16581	No damage	
Castor chair	EN ISO 4918	No damage	
Curly resultant to heat	EN ISO 23999	$\leq 8 $ mm	
Light fastness	EN ISO 105-B02	≥ 6	
Chemical resistance	EN ISO 26987	Not affected	
Underfloor heating		Suitable (subfloor temperature maximum 27°C)	
Sustainability performances			
Recyclability through ReStart®		Offcuts - Contact Tarkett for more information	
Recycled content		24 %	
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		6,12 kg CO ₂ eq /m ²	
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m ³)	Gold (≤ 100 µg / m ³)
Dimensions and designs			
Roll		Roll 1 x 23m	
Number of designs available		15	5

- Self-adhesive : reaction to fire Bfl-s1 on both substrates & Total VOC emissions-Platinum (≤ 10 µg/m³)
- Glue down : reaction to fire-Bfl-s1 on concret substrate and-Cfl-s1 on woodchip substrate. Total VOC emissions-Gold (≤ 100 µg / m³)



The above information is subject to modification for the benefit of further improvement (24/03/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.