

VENETO ACOUSTIC CORK xf^2 TM 15 dB (4.4 mm)

Datasheet

Classification	Norm	Tarkett Value
Product type		Plain and decorative linoleum on a corkment backing (EN 687)
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	42 General
Technical Characteristics	Norm	Tarkett Value
Country of origin		Italy
Surface treatment		xf^2
Total thickness	ISO 24346	4.4 mm
Total weight	ISO 23997	4.5 kg/m ²
Installation method		Glue-Down
Format Type		Roll
Performance for CE Marking	Norm	Tarkett Value
CE Marking		EN 14041
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Declaration of Performance #		0200 0025 DoP 2013 07
Thermal resistance (m ² •K/W)	ISO 10456	0,045 m ² •K/W
Technical Performance	Norm	Tarkett Value
Impact sound reduction - ΔL_w	EN ISO 717-2	15 dB
Castor chair effect	ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)
Underfloor heating		YES_27
Colour fastness to light	ISO 105-B02	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Phthalate - free		Yes
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum (≤ 10 $\mu\text{g} / \text{m}^3$)
Dimensions and designs		
Roll		Roll 2 x $\leq 32\text{m}$
Number of designs available		41



The above information is subject to modification for the benefit of further improvement (14/02/2022). Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com