


Veneto Silencio xf² 19dB (3.8mm)

Datasheet

Classification	Norm	Tarkett Value
Product type		Plain and decorative linoleum on a foam backing (EN 686)
Commercial classification	ISO 10874	33 Heavy
Industrial classification	ISO 10874	41 Moderate
Technical Characteristics	Norm	Tarkett Value
Country of origin		Italy
Surface treatment		xf ²
Total thickness	ISO 24346	3.8 mm
Total weight	ISO 23997	3.35 kg/m ²
Installation method		Glue-Down
Format Type		Roll
Performance for CE Marking	Norm	Tarkett Value
CE Marking		EN 14041
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Declaration of Performance #		0200 0027 DoP 2013 07
Thermal resistance (m ² ·K/W)	ISO 10456	0,042 m ² ·K/W
Technical Performance	Norm	Tarkett Value
Impact sound reduction - ΔL_w	EN ISO 717-2	19 dB
Castor chair effect	ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)
Underfloor heating		YES_27
Colour fastness to light	ISO 105-B02	≥ 6
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Phthalate - free		Yes
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Platinum (≤ 10 μg / m ³)
Dimensions and designs		
Roll		Roll 2 x ≤ 32 m
Number of designs available		14



The above information is subject to modification for the benefit of further improvement (14/02/2022). Tarkett reserves the right to maned this specification without giving prior notice. For the latest versions of the technical specifications, visit professional.tarkett.com