

# Woodstock Herringbone

## Datasheet

Classification	Norm	Tarkett Value
Product type	EN 13329	Laminate floor covering
Domestic classification	EN 13329	23 Heavy
Commercial classification	EN 13329	32 General
HDF core board density (minimum)	EN 13329	800 kg/m <sup>3</sup>
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN 13329 - Annex A	8 mm
Bevelled edges		4 sides
Locking system		Angling/Push down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0132-0091-DOP-2023-06
Reaction to fire	EN 14041	Cfl-s1
Slip resistance	EN 14041	Class DS ( $\mu \geq 0,30$ )
Thermal resistance	EN 14041 / EN 12667	$\leq 0,05 \text{ m}^2 \cdot \text{K/W}$
Content of Pentachlorophenol	EN 14041	< 5 ppm
Formaldehyde emission class	EN 14041 / EN 717-1	E1
Technical Performance	Norm	Tarkett Value
Abrasion resistance	EN 13329, annex E	AC4
Impact Resistance Big Ball	EN 13329, annex H / EN 17368	$\geq 750 \text{ mm}$
Impact Resistance Small Ball	EN 13329, annex H / EN 17368	$\geq 35 \text{ mm}$
Stain resistance - groups 1 and 2	EN 438	Level 5
Stain resistance - group 3	EN 438	Level 4
Furniture leg	ISO 16581	No damage
Castor chair	ISO 4918	No damage after 25000 cycles
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Thickness Swelling	ISO 24336	$\leq 18 \%$
Light fastness	NF EN 20105-A02	$\geq 4$
Residual indentation	EN ISO 24343-1	$\leq 0,05 \text{ mm}$
Surface Soundness	EN 13329, annex D	$\geq 1.25 \text{ N/mm}^2$
Sustainability performances	Norm	Tarkett Value
PEFC		Yes
French emissions label		A+
Total VOC Emissions (after 28 days)		Gold ( $\leq 100 \mu\text{g} / \text{m}^3$ )
CARB II Compliant		Yes
Dimensions and designs		
Plank	Plank 665 x 133mm - 14 planks=1,24 m <sup>2</sup> /box - 96 boxes/pallet	
Number of designs available	3	



The above information is subject to modification for the benefit of further improvement (04/01/2024). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.