

PRODUCT
SPECIFICATION
SHEET



THE ULTIMATE
FLOORING EXPERIENCE

Origins Plank™
Luxury Vinyl Flooring

PRODUCT SPECIFICATIONS

6"x36"

Wearlayer:	Tritonite™ (Urethane)
Nominal Thickness:	.080" (2 mm)
Gloss:	Matte Satin
Edge Treatment:	Rolled
Square Feet per Carton:	27
Weight per Carton (Lbs.):	20
Cartons per Pallet:	100
ASTM F-970 Static Load Limit:	250 lbs/in ² (113.4 kg)
FloorScore® Certification SCS-EC10.2-2007:	SCS-FS-01338
Design Available:	Good Living Plank
SPECIFI Designs Available:	Quarter Mix Oak, Rock Maple, Fruitwood (Only Available in 4"x36")



INSTALLATION

Use:	Residential and Light Commercial
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Adhesive:	Tarkett QBond-One™
Adhesive Application:	Residential Dry Set – Apply adhesive with a 1/16" deep x 1/16" wide x 1/16" apart square notched trowel or medium nap paint roller and allow adhesive to dry until it is tacky to the touch. Light Commercial Wet Set - Apply adhesive with a 1/32" deep x 1/16" wide x 1/32" apart notched trowel. Place flooring into adhesive immediately after application.

- Maintain the work area, flooring and adhesive between 65° F and 85° F (18°C - 30°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Use only cementitious based patching and leveling compounds.
- Cartons shall be stored horizontally at all times.
- To ensure the best color match when installing two or more cartons, make sure run numbers on each carton are the same.
- Tarkett QBond-One is used as a dry-set application only in residential applications, and is used as a wet-set application in light commercial settings.
- Roll flooring in both directions with a 75 lbs. (34 kg) 3-section floor roller.
- Refer to Tarkett Luxury Flooring Installation Manual for complete and detailed installation instructions.

CARE AND MAINTENANCE

- **Do not walk on floor for 48 hours after installation.**
- Do not replace frequently moved furniture or allow heavy traffic for at least 24 hours
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. **Do not use felt pads.**
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.

15 YEAR LIMITED WARRANTY, RESIDENTIAL USE

- The following categories are covered for a residential usage with a 15 year limited warranty for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to our Consumer Protection Guide on TarkettNA.com for complete information.

Residential Limited Warranty		Light Commercial Limited Warranty
Wear and Manufacturing Defects	Rip, Tear, Gouge and Indent	Wear
Traffic/Asphalt Stain	Common Household Stain	Manufacturing defects
Moisture Stain (Concrete only)	Shoe Scuff	