

PRODUCT SPECIFICATION SHEET



THE ULTIMATE
FLOORING EXPERIENCE

Vista™ Luxury Vinyl Flooring



PRODUCT SPECIFICATIONS

TILE

PLANK

| | | |
|---|-------------------------|-------------------------|
| Wearlayer: | Tritonite™ (Urethane) | Tritonite™ (Urethane) |
| Nominal Thickness: | .080" (2 mm) | .080 (2 mm) |
| Gloss: | Matte Satin | Matte Satin |
| Edge Treatment: | GroutFit® | Rolled |
| Size: | 16"x16" (40.6x40.6cm) | 6"x36" (15.2x91.4cm) |
| Square Feet per Carton: | 26.7 (2.4 sq. meters) | 27 (2.5 sq. meters) |
| Weight per Carton (Lbs.): | 20 (9kg) | 20 (9kg) |
| Cartons per Pallet: | 60 | 50 |
| ASTM F-970 Static Load Limit: | 250 lbs/in ² | 250 lbs/in ² |
| ASTM E-648 Flooring Radiant Panel: | Class 1 | Class 1 |
| ASTM E-662 Smoke Density: | <450 | <450 |

INSTALLATION

| | |
|------------------------------|---|
| Use: | Residential and Light Commercial |
| Location: | Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors. |
| Adhesive: | Tile or Plank - Tarkett QBond-One™ |
| Adhesive Application: | <p>Residential Dry Set – Apply adhesive with a 1/16" deep x 1/16" wide x 1/16" apart square notched trowel or medium nap paint roller and allow adhesive to dry until it is tacky to the touch.</p> <p>Light Commercial Wet Set - Apply adhesive with a 1/32" deep x 1/16" wide x 1/32" apart notched trowel. Place flooring into adhesive immediately after application.</p> |

- Maintain the work area, flooring and adhesive between 65° F and 85° F (18°C – 29.4°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Cartons shall be stored horizontally at all times.
- To insure the best color match when installing two or more cartons, make sure run numbers on each carton are the same.
- Use only cementitious based patching and leveling compounds.
- Tarkett QBond-One is a dry-set adhesive used for installation of tile in residential and light commercial applications.
- Tarkett QBond-One is a dry-set adhesive used for installation of plank in residential applications and a wet-set adhesive used for installation of plank in light commercial applications.
- Use Tarkett QBond-One when installing over radiant heated floors.
- Roll flooring in both directions with a 75-100 lb. (34-45kg) sectional floor roller.
- Refer to Tarkett Luxury Flooring Installation Manual for complete and detailed installation instructions.

CARE AND MAINTENANCE

- **Do not was floor for 48 hours after installation.**
- Do not replace frequently moved furniture or allow heavy traffic for at least 24 hours
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. **Do not use felt pads.**
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.

15 YEAR LIMITED RESIDENTIAL EXTREME PERFORMANCE WARRANTY, 5 YEAR LIMITED LIGHT COMMERCIAL

- The following categories are covered for a residential usage with a 15 year limited warranty for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to our Consumer Protection Guide on TarkettNA.com for complete information.

| Residential Limited Warranty | | Light Commercial Limited Warranty |
|--------------------------------|-----------------------------|-----------------------------------|
| Wear and Manufacturing Defects | Rip, Tear, Gouge and Indent | Wear |
| Traffic/Asphalt Stain | Common Household Stain | Manufacturing defects |
| Moisture Stain (Concrete only) | Shoe Scuff | |