

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Millwork Wall Finishing System profiles replicate the look of finely milled wood.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
 30000 Aurora Rd.
 Solon, Ohio 44139
 Web: www.tarketta.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Millwork Resilient Wall Base is manufactured from a proprietary thermoplastic rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861 Standard Specification for Resilient Wall Base, Type TP, and Group 1.

1.3.2. **Physical Characteristics:** Wall Base

Attache™ (MW-XX-E): 1/4" (.25", 6.35mm) thick, by 6" (15.24cm) height, 8 per carton, 8 ft lengths, 64 ft (19.5m) per carton, 57 lbs (26.0kg) per carton

Ambassador™ (MW-XX-K): 3/8" (.375", 9.52mm) thick by 4" (10.16cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 42 lbs (19.1kg) per carton

Delineate™ (MW-XX-T): 0.400" (10.2 mm) thick by 4-1/4" (10.8 cm) height, and 8 ft lengths

Emissary™ (MW-XX-P): 37/64" (.531", 13.49mm) thick by 4-1/2" (20.32cm) height, 6 per carton, 8 ft lengths, 48 ft (12.9m) per carton, 60 lbs (22.7kg) per carton

Envoy™ (MW-XX-L): 3/4" (.75", 19.05mm) thick by 5-1/2" (13.97cm) height, 4 per carton, 8 ft lengths, 32 ft (9.75m) per carton, 66 lbs (29.9kg) per carton

Equinox™ (MW-XX-R): 3/8" (.375", 9.53mm) thick by 4-1/2" (11.43cm) height, 5 per carton, 8 ft lengths, 40 ft (10.16m) per carton, 50 lbs (22.7kg) per carton

Inflection™ (MW-XX-G): 3/8" (.375", 9.52mm) thick by 5-1/4" (13.34cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 65 lbs (29.5kg) per carton

Mandalay™ 2-1/2" (MW-XX-H25): 3/8" (.375", 9.52mm) thick by 2-1/2" (6.35cm) height, a rectangular shaped profile with a 45° chamfer top, 5 per carton, 8 ft lengths, 40 ft (12.2m) per carton, 40 lbs (18.14kg) per carton

Mandalay™ 3" (MW-XX-H3): 3/8" (.375", 9.52mm) thick by 3" (7.62cm) height, a rectangular shaped profile with a 45° chamfer top, 7 per carton, 8 ft lengths, 56 ft (17.1m) per carton, 48 lbs (21.8kg) per carton

Mandalay™ 4-1/2" (MW-XX-H): 3/8" (.375", 9.52mm) thick by 4-1/2" (11.43cm) height, a rectangular shaped profile with a 45° chamfer top, 5 per carton, 8 ft lengths, 40 ft (12.2m) per carton, 52 lbs (23.6kg) per carton

Mandalay™ 6" (MW-XX-H6): 3/8" (.375", 9.52mm) thick by 6" (15.24cm) height, a rectangular shaped profile with a 45° chamfer top, 4 per carton, 8 ft lengths, 32 ft (9.75m) per carton, 54 lbs (24.5kg) per carton

Monarch™ (MW-XX-M): 3/16" (.19", 4.76mm) thick by 6.0" (15.24cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 46 lbs (20.9kg) per carton

Monarch™ 8" (MW-XX-M8): 3/16" (.19", 4.76mm) thick by 8.0" (15.24cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 60 lbs (27.2kg) per carton

Monument™ 2-1/2" (MW-XX-S25): 1/4" (.250", 6.35mm) thick by 2 1/2" (6.35cm) height, a rectangular shaped profile, 8 per carton, 8 ft lengths, 64 ft (19.5m) per carton, 33 lbs (18.14kg) per carton

Monument™ 4" (MW-XX-S4): 1/4" (.250", 6.35mm) thick by 4" (10.16cm) height, a rectangular shaped profile, 8 per carton, 8 ft lengths, 64 ft (19.5m) per carton, 50 lbs (21.8kg) per carton

Oblique™ (MW-XX-N): 3/8" (.375", 9.53mm) thick by 3" (7.62cm) height with a 45° angular top, 7 per carton, 8 ft lengths, 56 ft (17.0m) per carton, 42 lbs (19.1kg) per carton

Overlook™ (MW-XX-C): 1/4" (.25", 6.35mm) thick by 7-1/2" (19.05cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 56 lbs (25.4 kg) per carton

Outline™ (MW-XX-D): 5/16" (.313", 7.92mm) thick by 3-1/2" (8.89cm) height, 10 per carton, 8 ft lengths, 80 ft (24.4m) per carton, 47 lbs (21.3kg) per carton

Reveal™ 4-1/4" (MW-XX-F): 1/4" (.25", 6.35mm) thick by 4-1/4" (10.8cm) height with a 45° angular top and a 7/32" (5.5mm) wide surface reveal, 8 per carton, 8 ft lengths, 64 ft (19.5m) per carton, 50 lbs (22.7kg) per carton

Reveal™ 6" (MW-XX-F6): 1/4" (.25", 6.35mm) thick by 6" (15.24cm) height with a 45° angular top and a 7/32" (5.5mm) wide surface reveal, 8 per carton, 8 ft lengths, 64 ft (19.5m) per carton, 58 lbs (26.3kg) per carton

Reveal™ 8" (MW-XX-F8): 1/4" (.25", 6.35mm) thick by 8" (20.32) height with a 45° angular top and a 7/32" (5.5mm) wide surface reveal, 4 per carton, 8 ft lengths, 32 ft (9.75m) per carton, 49 lbs (14.5kg) per carton

Silhouette™ (MW-XX-J): 1/2" (.50", 12.7mm) thick and 4" (10.16cm) height, 6 per carton, 8 ft lengths, 48 ft (14.63m) per carton, 42 lbs (19.1kg) per carton

1.3.3. Physical Characteristics (Chair Rail):

Rampart (CHR-XX-C): 4" (10.16cm) wide by 3/8" (9.53mm) thick profile, 8 ft. (2.4m), 5 per carton [40 ft (12.2m) per carton], and 6 lbs (2.72kg) per piece [36 lbs (16.3kg) per carton]

1.3.4. Physical Characteristics (Corner Guard):

VBG-XX-C: 90° angular shaped profile with 1-1/4" (3.18cm) return legs, 1/4" (6.35mm) leg thickness

1.3.5. Physical Characteristics (Quarter Round/Shoe Moulding):

QTR-XX-A: 1/2" (12.7 mm) wide by 1/2" (12.7 mm) high radius profile with a pressure sensitive adhesive backing, length is 8 ft. (2.49 m), 20 lengths [160 ft. (48.8 m)] per carton; weight of carton is 24 lbs (10.9 kg).

QTR-XX-D: 3/4" (19.05 mm) wide by 3/4" (19.05 mm) high radius profile with a pressure sensitive adhesive backing, length is 8 ft. (2.49 m), 10 lengths [140 ft. (42.67 m)] per carton, weight of carton is 30 lbs (13.6 kg).

SHU-XX-A: 1/4" (6.4 mm) wide by 1-1/2" (3.8 cm) high radius profile, 8 ft. (2.4 m) lengths with pressure sensitive adhesive backing, 10 lengths [80 ft. (24.4 m) - 21 lbs. (9.5 kg)] per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.2. Millwork Wall Base meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in ASTM F-1861.
- 2.3. **Flexibility:** Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.
- 2.4. **Chemical resistance (ASTM F 925):** Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution
- 2.5. **Resistance to light (ASTM F 1515):** $\Delta E < 8$
- 2.6. **Fire Resistance:**
 - ASTM E 84 Flame/Smoke (NFPA 255): Class B, ≤ 450
 - ASTM E 648 Critical Radiant Flux (NFPA 253): Class I

3. INSTALLATION

- 3.2. See Tarkett Millwork wall base installation instructions for complete details.

3.3. Adhesives:

960 Cove Base Adhesive (Porous surfaces)

| Profiles | Total ft/gallon |
|----------------------|-----------------|
| MW-XX-A (Diplomat) | = 175 - 225 lf |
| MW-XX C (Overlook) | = 95 - 145 lf |
| MW-XX D (Outline) | = 230 - 280 lf |
| MW-XX E (Attaché) | = 125 - 175 lf |
| MW-XX F (Reveal) | = 185 - 235 lf |
| MW-XX F6 (Reveal) | = 125 - 175 lf |
| MW-XX F8 (Reveal) | = 85 - 135 lf |
| MW-XX G (Inflection) | = 145 - 195 lf |
| MW-XX-H25 (Mandalay) | = 335 - 385 lf |
| MW-XX-H3 (Mandalay) | = 275 - 325 lf |
| MW-XX-H (Mandalay) | = 175 - 225 lf |
| MW-XX H6 (Mandalay) | = 125 - 175 lf |
| MW-XX J (Silhouette) | = 200 - 250 lf |
| MW-XX K (Ambassador) | = 200 - 250 lf |
| MW-XX L (Envoy) | = 140 - 190 lf |
| MW-XX M (Monarch) | = 125 - 175 lf |
| MW-XX M8 (Monarch) | = 85 - 135 lf |
| MW-XX N (Oblique) | = 275 - 325 lf |
| MW-XX P (Emissary) | = 175 - 225 lf |
| MW-XX-R (Equinox) | = 175 - 225 lf |
| MW-XX T (Delineate) | = 185 - 235 lf |

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush or roller

Approximate coverage:

- 1 kg Unit (0.95 Qt.) – 24 to 36 sq. ft.
- 6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Millwork Resilient Wall Base Installation & Maintenance Instructions for complete maintenance details.



7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

info@tarkettna.com

www.tarkettna.com