



Angle Fit™ Rubber Stair Treads without Riser

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Rubber Stair Treads A.D.A., Visually-Impaired, and California Title 24 Compliant.

1.1. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.2. **Proprietary Product Description:**

1.1.1. **Construction:** Tarkett Rubber Stair Treads are manufactured from a homogeneous composition of 100% synthetic rubber, high quality additives, and colorants to meet the performance requirements of ASTM F2169 Standard Specification for Resilient Stair Treads, Type TS, Class 1 and 2, Group 1 and 2. All Tarkett Stair Treads are available with a 2" (5.08 cm) wide strip of contrasting color to comply with A.D.A. and Visually-Impaired. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements.

NOTE: 0.080" (2 mm) thick vinyl risers are recommended for the following rubber stair treads.

1.2.1. **Styles & Physical Characteristics:**

Bamboo Texture Square Nose Rubber Stair Tread (BMNT), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VIBMNT with 2" (5.0 cm) wide contrasting color grit tape insert.

VIBMNTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Bamboo Round Nose Rubber Stair Tread (BMT), .210" (5.33 mm) to .113" (2.87 mm), tapered 13" (33 cm) tread depth.

For visually impaired specify:

VIBMT with 2" (5.0 cm) wide contrasting color grit tape insert.

VIBMTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Cubis Texture Square Nose Rubber Stair Tread (CUBT), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VICUBT with 2" (5.0 cm) wide contrasting color grit tape insert.

VICUBTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Cubis Texture Round Nose Rubber Stair Tread (CUT), .210" (5.33 mm) to .113" (2.87 mm), tapered 13" (33 cm) tread depth.

For visually impaired specify:

VICUT with 2" (5.0 cm) wide contrasting color grit tape insert.

VICUTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Diamond Square Nose Rubber Stair Tread (CNN), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VICNN with 2" (5.0 cm) wide contrasting color grit tape insert.

VICNNS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Diamond Round Nose Rubber Stair Tread (CN), .210" (5.33 mm) to .113" (2.87 mm), tapered 13" (33 cm) tread depth.

For visually impaired specify:

VICN with 2" (5.0 cm) wide contrasting color grit tape insert.

VICNS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Fast Lane Surface Texture Square Nose Rubber Stair Tread (CFLNT), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VICFLNT with 2" (5.0 cm) wide contrasting color grit tape insert.

VICFLNTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Fast Lane Surface Texture Round Nose Rubber Stair Tread (CFLT), .210" (5.33 mm) to .113" (2.87 mm), tapered 13" (33 cm) tread depth.

For visually impaired specify:

VICFLT with 2" (5.0 cm) wide contrasting color grit tape insert.

VICFLTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip



Angle Fit™ Rubber Stair Treads without Riser

Product Specification

Hammered Pattern Rubber Stair Tread (HMNT), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VIHMNT with 2" (5.0 cm) wide contrasting color grit tape insert

VIHMNTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Hammered Pattern Rubber Stair Tread Extended Depth (HMNTD), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 14" (35.56 cm) tread depth

For visually impaired specify:

VIHMNTD with 2" (5.0 cm) wide contrasting color grit tape insert

VIHMNTDS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Rice Paper Texture Square Nose Rubber Stair Tread (FRPANT), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VIFRPANT with 2" (5.0 cm) wide contrasting color grit tape insert.

VIFRPANTS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Rice Paper Texture Round Nose Rubber Stair Tread (FRPAT), Round nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 13" (30.48 cm) tread depth.

For visually impaired specify:

VIFRPAT with 2" (5.0 cm) wide contrasting color grit tape insert.

VIFRPATS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Round Raised Disk Pattern Rubber Stair Tread (RNRD): 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth

For visually impaired specify:

VIRRD with 2" (5.0 cm) wide contrasting color grit tape insert

VIRRDS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Square Raised Disk Pattern Rubber Stair Treads (RNSQ), 2" (5.08 cm) hinged square nose configuration, .210" (5.33 mm) to .113" (2.87 mm) tapered 12" (30.48 cm) tread depth.

For visually impaired specify:

VIRSQ with 2" (5.0 cm) wide contrasting color grit tape insert

VIRSQS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

SN Service Weight Rubber Stair Treads, Square nose configuration is 1-5/8" (4.66 cm) with a hinge, 3/16" (4.76 mm) to 1/8" (3.17 mm) tapered 13-1/4" (33.66cm) tread depth. [Available with a Visually Impaired (**VISN**) 2" (5.0 cm) wide contrasting color grit tape or solid color rubber insert.]

SAN Service Weight Safe-T-Grip Rubber Stair Treads 1-5/8" (4.66 cm) square nose configuration, 3/16" (4.76 mm) to 1/8" (3.17 mm) tapered 13-1/4" (33.66 cm) tread depth, Two 1" (2.5 cm) wide grit tape inserts.

1.1.2. Sizes:

Rubber stair treads available in 3', 3-1/2', 4', 4-1/2', 5', and 6' (0.91 m, 1.07 m, 1.22 m, 1.37 m, 1.52 m, and 1.83 m)

NOTE: Specify 0.080" (2 mm) Vinyl Risers with the above stair treads.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A
- 2.2. **Abrasion Resistance** (ASTM D 3389): Passes
- 2.3. **Slip Resistance** (ASTM D 2047): Meets and exceeds a static coefficient of friction of 0.8
- 2.4. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux): Class 1 (Minimum 0.45 W/cm²)
- 2.5. **Smoke Development** (ASTM E 662/NFPA 258): less than 450
- 2.6. **Canadian Flammability & Smoke** (CAN/ULC S102.2):
≤ 300 Flame Spread & ≤ 500 Smoke Developed

3. INSTALLATION

See Tarkett Stair Tread installation instructions for complete details.

3.1. Adhesives:

- **Tarkett 965 Adhesive Coverage:**
Porous Substrate: 125-150 sq. ft. per gallon
Non-porous Substrate: 150-175 sq. ft. per gallon
- **Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)
Application: Brush or roller
Approximate coverage:
1 kg Unit (0.95 Qt) – 24 to 36 sq. ft.
6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft.
- **Tarkett 930 Two-Part Epoxy Caulking Compound**
Application: 30 oz. cartridge (Use Tarkett 530 dual-cartridge dispenser gun with cartridge)
Coverage: Approximately 50 linear ft. /cartridge

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.



Angle Fit™ Rubber Stair Treads without Riser

Product Specification

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Rubber Stair Tread Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

info@tarkettna.com

www.tarkettna.com