PRODUCT DATA SHEET

CARPET TILES

Desso Desert ProBase[®]





Textured carpet tile to create serene flooring

Desso Desert lends a feeling of vast, open spaces to the indoors with its subtly layered organic design.

Like the shifting sands of the desert, this textured carpet tile allows you to play with the space to create a serene flooring scheme in nine weathered hues ranging from a warm neutral shade and muted mushroom to light grey and deep charcoal.





Desso Desert ProBase[®]

| Product Characteristics | Standards | Desso Desert ProBase® |
|---------------------------------------|-----------|--|
| Product construction | ISO 2424 | Structured loop pile |
| Dye method | ISO 2424 | Solution dyed |
| Pile fibre composition | ISO 2424 | BCF Polyamide 6 and ECONYL [®] (ECONYL [®] is made from 100% regenerated content) |
| Gauge | ISO 2424 | 1/10 |
| Primary backing | ISO 2424 | Polyester fleece |
| Secondary backing | ISO 2424 | Desso Probase Polyver® |
| Number of Tufts | ISO 1763 | 1580/dm ² |
| Total pile weight | ISO 8543 | 590 g/m² 17.4 oz /yd² |
| Total weight | ISO 8043 | 4200 g/m² |
| Pile weight above the substrate | ISO 8543 | 405 g/m² |
| Surface pile density | ISO 8543 | 0.131 g/cm ³ |
| Thickness of pile above the substrate | ISO 1766 | 3.1mm |
| Total thickness | ISO 1765 | 6.0mm |
| Dimension | EN 994 | 500 x 500mm |
| Tiles per box/area | | 20/5m ² |
| Warranty | | 10 years |
| LVR | | Available upon application |

| Performance Characteristics | Standards | Desso Desert ProBase® |
|-------------------------------------|---------------------|---|
| Reaction to fire | ISO AS 9239-1: 2003 | Critical radiant flux 8.6 kW/m² Smoke 140%.min |
| Electrostatic properties | ISO 6356 | ≤ 0.2 kV |
| Thermal resistance | ISO 8302 | 0.059 m² K/W |
| Dimensional stability | EN 986 | ≤ 0.2% |
| Sound absorption | ISO 354 | α _w = 0.15 |
| Impact sound reduction ΔL_w | ISO 10140 | 24 dB |

Recommended specification clauses for your project

Tarkett product numbers starting with 71056

- 1. Solution dyed nylon carpet tile 500mm x 500mm with $\mathsf{ProBase}^{\$}$ backing
- 2. 10 year commercial manufacturer's product warranty
- 3. Contractor must confirm lead times with the manufacturer

For information on our full range, contact us on 1300 851 484 or visit Tarkospec.com.au The information in this data sheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.

