


Granit Multisafe

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Homogeneous Vinyl floor covering
Binder content	ISO 10581	Type I
Commercial classification	ISO 10874	31 Moderate
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2,50 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	3010 g/m²
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0019-0034-DoP-2013-07
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 10.8kW/m² Smoke 14%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	0,010 m²·K/W
Technical Performance	Norm	Tarkett Value
Marine Equipment	IMO 2010 FTP Code part 2 and 5	Approved
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm Best measured value: 0,02 mm
Slip resistance	DIN 51130 DIN 51097 AS 4586	R10 Class B ***
Curl resultant to heat	EN ISO 23999	≤ 8 mm
Colour fastness to light	ISO 105-B02	≥ 7
Dimensional stability	EN ISO 23999	Average Measured Value : ≤ 0.40 %
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Wetroom approval	EN 13553 Annex A	Watertight
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Sustainability performances	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5,26 kg CO ₂ eq /m²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		3,60 kg CO ₂ e /m² /year
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m³)
Formaldehyde emission		E1
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs		
Roll		Roll 2 x 25 m
Number of designs available		8

*** Profiled surfaces such as Granit Multisafe are not appropriate to test using a pendulum method and should utilise barefoot inclining platform test



For Global Green Tag certificates please see the Tarkett Australia page at globalgreentag.com

The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.