

MULTISAFE AQUA

SLIP RESISTANT VINYL FOR BAREFOOT BATHROOM APPLICATIONS

Using a new surface-embossing technology that provides innovative slip-resistance, Multisafe Aqua is a designer floor for use in wet areas. Treated with Top Clean surface protection for easy maintenance and resistance to scratches and stains. Multisafe Aqua is perfect for barefoot applications such as bathrooms in aged care and hospitals.



More excellent reasons to choose Multisafe Aqua

- ✓ Next generation surface embossing
- ✓ Stone and fibre wood designs
- ✓ Slip resistance Barefoot Class C
- ✓ Slip resistance P3
- ✓ Hygienic and easy to maintain
- ✓ TVOC ≤ 100 µg/m³ after 28 days
- ✓ 100% Phthalate free

SPECIFICATION DATA

Using a new surface-embossing technology that provides innovative slip-resistance, Multisafe Aqua is a designer floor for use in wet areas such as collective showers, locker rooms, collective housing and healthcare facilities. Treated with our Top Clean surface protection for easy maintenance and resistance to scratches and stains. Colour-coordinated with our Aquarelle Wall HFS range.

TECHNICAL DATA	STANDARD	MULTISAFE AQUA
CLASSIFICATION		
Classification	EN 649	Compact slip resistant heterogeneous for use in wetroom
	EN 14041	YES
	EN ISO 10874 - EN 685	
	Commercial	33
	Industrial	42
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	2.00 mm
Total weight	EN ISO 23997	3100 g/m ²
Wear layer thickness	EN ISO 24340	0.55 mm
Form of delivery	EN ISO 24341 (rolls)	20 lm x 2m
TECHNICAL PERFORMANCES		
Dimensional Stability	ISO 23999 - EN 434	≤ 0.10%
Chemical resistance	EN ISO 26987	Good
Curl Resistance	Yes	≤ 8mm
Reaction to fire	AS/ISO 9239.1	Critical Radiant Flux 8.6kW/m ² Smoke 114 %.minutes
Static electrical discharge	EN 1815	≤ 2.0 kV antistatic on concrete
Thermal resistance	EN 12667	0.01 m ² K/W
Residual indentation	Average measured value ISO 24343-1 - EN 433 Requirement	≤ 0.10 mm ≤ 0.10 mm
Barefoot test	NF EN ISO 717 / 2	Class C: Designs stone and fiber wood
Pendulum slip test	AS 4586:2013	P3
seam strength	EN 684	Average value: ≥ 240N/50mm
Light fastness	EN ISO 105-B02	≥ 6
Underfloor heating		Suitable - Max 27 deg C

The above information is subject to modification for the benefit of further improvement. (02/19)

It is essential that the product is installed fully to the manufacturers instructions. Maintenance instructions, recommended adhesives and further information are available from the technical department.



Disclaimer : Please note that products in photos are installed for creative purposes and not according to technical specifications. Please refer to Tarkett installation instructions for guidance.