

Primo Premium

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Homogeneous vinyl floor covering
Binder content	ISO 10581	Type I
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	Norm	Tarkett Value
Surface treatment		PUR Reinforced
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	2900 g/m ²
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0019-0018-DoP-2013-07
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 10.5W/m ² Smoke 62%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	~0,010 m ² ·K/W
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: $\leq 0,10$ mm Best measured value: 0,03 mm
Slip resistance	AS 4586	P4
Slip resistance	DIN 51130	R10
Curl resultant to heat	EN ISO 23999	≤ 18 mm for rolls
Clean room	ISO 14644-1	ISO class 4
Castor chair	ISO 4918	Suitable
Colour fastness to light	ISO 105-B02	≥ 6
Dimensional stability	EN ISO 23999	Measured Value : ≤ 0.40 % for rolls
Ease of Decontamination	ISO 8690 – DIN 25415	Excellent
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (maximum 27°C)
Wetroom approval	EN 13553 Annex A	Watertight
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5,71 kg CO ₂ eq /m ²
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m ³)
Formaldehyde emission		E1
GreenTag		Level A
Health Rate		Platinum
Dimensions and designs		
Roll	Roll 2 x 23 m	
Number of designs available	36	



For Global Green Tag certificates please see the Tarkett Australia page at globalgreentag.com

The above information is subject to modification for the benefit of further improvement (4/11/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia
Suite 1, Level 3, 3 Columbia Court, Baulkham Hills NSW 2153
(02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au

