

CARPET
PLANKS

Desso
Traverse
EcoBase®



Transform simple diagonals into endless opportunities

Imitating the tactile character of fashion fabrics, Desso Traverse's all-over two directional design provides a carpet solution that gives endless options to create distinct and calm floors.

The combination of dense yarn fused with the random intertwining of thin black thread gives this carpet tile a flexible, tactile structure.

Desso Traverse is available in 15 colours, with a strong core of neutral colours; brighter red, blue and yellow tones bring liveliness to the range that forms part of the Materials in Touch collection.

Desso Traverse is a Silver Cradle to Cradle® certified carpet plank as it's supplied with EcoBase® backing.



Product Characteristics	Standards	Desso Traverse EcoBase®
Product construction	ISO 2424	Structured loop pile
Dye method	ISO 2424	Solution dyed
Pile fibre composition	ISO 2424	BCF Polyamide 6 ECONYL®
Gauge	ISO 2424	1/10"
Primary backing	ISO 2424	Polyester fleece
Secondary backing	ISO 2424	Desso EcoBase®
Number of stitches	ISO 1763	2130/dm ²
Total pile weight	ISO 2424	675 g/m ² 19.9 oz/yd ²
Total weight	ISO 8543	4200 g/m ²
Pile weight above the substrate	ISO 8543	565 g/m ²
Surface pile density	ISO 8543	0.123 g/cm ³
Thickness of pile above the substrate	ISO 1766	4.6mm
Total thickness	ISO 1765	7.0mm
Dimension	EN 994	1000 x 250mm
Planks per box/area		16/4m ²
Warranty		10 years
LVR		Available upon application

Performance Characteristics	Standards	Desso Traverse EcoBase®
Reaction to fire	ISO AS 9239-1	Critical radiant flux 3.5 kW/m ² Smoke 36%.min
Electrostatic properties	ISO 6356	≤ 2.0 kV
Thermal resistance	ISO 8302	0.081 m ² K/W
Dimensional stability	EN 986	≤ 0.2%
Sound absorption	ISO 354	$\alpha_w = 0.20$
Impact sound reduction	ISO 10140	$\Delta L_w 25dB$

Recommended specification clauses for your project

Tarkett product number starting with 710712

1. Solution dyed Nylon carpet plank 1000mm x 250mm with EcoBase backing
2. Must be installed as per manufacturer's instructions

For information on our full range, contact us on 1300 851 484
or visit Tarkospec.com.au

The information in this data sheet is correct at date of publication however, due to Tarkett's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Tarkett's instructions regarding installation, cleaning and maintenance must be observed. Please contact Tarkett for further information on these instructions.