iD
Naturals 70

Ultimate durability

Ultra matte finish

Minimal visible pattern repeat

Nature inspired designs

High defenition printing

WWW.TARKETT.COM.AU

LUXURY VINYL TILES

⊘ Tarkett

iD Naturals 70
Technical Datasheet

Classification	Standards	iD Naturals 70
Product Type	EN ISO 10582	Heterogeneous poly (vinyl chloride) floor covering
Classification	EN ISO 10874	Domestic: 23 Commercial: 34 Industrial: 43

Technical Characteristics	Standards	iD Naturals 70
Total thickness	EN ISO 24346	2.5mm
Wear layer thickness	EN ISO 24340	0.70mm
Total weight	EN ISO 23997	3950 g/m²
Wear Layer Binder content	EN ISO 10582	Type I
Surface treatment		TEKTANIUM™
High definition digitally printed		Yes
Bevelled edges		Yes
Installation method		Glue-Down

Performance for CE Marketing Requirements	Standards	iD Naturals 70
Declaration of performance	EN 14041	0132-0085-DoP-2020-03

Technical Performances	Standards	iD Naturals 70
Dimensional stability	EN ISO 23999	≤ 0.10%
Curl resistant to heat	EN ISO 23999	≤ 2.0mm
Reaction to fire	EN 13501-1	Critical radiant flux 9.3 kW/m² Smoke 161%.min
Furniture leg	EN 424	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction	EN 1SO 717/2	ΔLw 3dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85dB)
Residual indentation	EN ISO 24343-1	≤ 0.05 mm
Thermal resistance	EN ISO 10456	0.02 m² ·K/W per single tile
Colour fastness to light	EN ISO 105-B02 (method 3ª)	≥ 6
Chemical resistance	EN ISO 26987	Excellent Resistance
Slip resistance	DIN 51130/EN 13893 AS 4586	P9/R10 depending on embossing μ > 0.3 P4/P5 depending on embossing
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Static electrical propensity	EN 1815	Antistatic (≤ 2kV)
Underfloor heating		Suitable - max. 27ºC

Sustainability Performances	Standards	iD Naturals 70
Recycled Content		39.5%
Recylcable		Yes - Installation waste
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		7.71kg CO₂eq /m²
Phthalate		Not Detected
Total VOC emissions	EN 16516	Platinum (≤ 10 µg/m³)
Material health statement		Available

Dimensions	Standards	iD Naturals 70
Tiles		500 x 500mm - 15 tiles/box = 3.75m² 500 x 1000mm - 7 tiles/box = 3.50m² 333.3 x 666.6mm - 16 tiles/box = 3.55m² 666.6 x 666.6mm - 8 tiles/box = 3.55m²
Planks		200 x 1200mm - 15 planks/box = 3.60m² 285 x 1200mm - 11 planks/box = 3.76m² 250 x 1500mm - 10 planks/box = 3.75m²

The above information is subject to modification for the benefit of further improvement. (05/25).Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please note that products in the photos are installed for creative purposes and not according to technical specifications.