

Starfloor Click 30

Starfloor Click 55

LUXURY VINYL TILES

TECHNICAL DATA	STANDARD	Starfloor Click 30	Starfloor Click 55
CLASSIFICATION			
Classification	EN ISO 10582	Heterogeneous PVC Compact floor covering	
	EN ISO 10874	Residential: 23 Commerical: 31	Residential: 23 Commerical: 33
Wear Layer binder content	EN ISO 10582	Type I	
TECHNICAL CHARACTERISTICS			
Total thickness	EN ISO 24346	4.00 mm	5.00 mm
Wear layer thickness	EN ISO 24340	0.30 mm	0.55 mm
Total weight	EN ISO 23997	7400 g/m²	9200 g/m²
Bevelled edges		Microbevels	
Embossing in register		Yes on EIR references	
Surface treatment (PUR)		Extreme®	
Form of delivery	EN ISO 24342 Planks	122 x 18.3 cm = 9 planks/box = 2.01m²	122 x 18.3 cm = 7 planks/box = 1.56 m²
	EN ISO 24342 Tiles	60.05 x 31 cm = 9 tiles/box = 1.68m²	60.05 x 31 cm = 9 tiles/box = 1.68m²
TECHNICAL PERFORMANCES			
Reaction to fire	EN 13501-1	Bfl-s1 loose laid on concrete and wood	
Electrostatic properties	EN 1815	< 2 kV on concrete	
	EN 1081	> 10 ⁹ Ohm	
Slip resistance	EN 13893	μ ≥ 0,30	
	DIN 51130	R9 / R10 depending on embossing	
Thermal resistance	EN ISO 10456	0.03 m2. K/W	0.04 m2. K/W
Dimensional stability	EN ISO 23999	≤ 0.10 %	
Impact sound reduction	EN ISO 717/2	Δ Lw = 3 dB	
Residual Indentation	EN ISO 24343-1	≤ 0.08 mm	
Furniture leg	EN 424	No damage	
Castor chair	ISO 4918 (EN 425)	No damage	
Curl resultant to heat 6h at 80°C (mm)	EN ISO 23999	≤ 2.00 mm	
Underfloor heating		Suitable – max. 27°C	
Light fastness	EN ISO 105-B02	≥ 6	
Resistance to chemicals	EN ISO 26987	Good resistance	
ENVIRONMENTAL PERFORMANCES			
Total VOC emissions	ISO 16000-9	≤ 100µg/m³	
COLOURS			
		Wood: 25	
		Stone & Ceramic: 15	

The above information is subject to modification for the benefit of further improvement (02/2025).
 For the latest information, please visit our website: www.Tarkett-asia.com
 Tarkett's instructions regarding installation, cleaning and maintenance should be observed.








STFC 55



STFC 30




