

Tandus Centiva



TILE + PLANK

ADAPTT WOODLOT


SPECIFICATIONS

Classification:	ASTM F1700 Class III Type B
Total Thickness:	0.177" (4.5 mm)
Wear Layer Thickness:	20 mil (0.5 mm)
Edge Treatment:	Microbeveled
Emboss:	Standard Emboss
Urethane:	Factory Applied
Warranty:	10-Year Limited Commercial Wear Warranty
Colors:	20



Products shown: SSP 2321, 2320 & 2319

Installation Methods:



SIZES	7.25" x 48" (18.415 cm x 121.92 cm) 6" x 36" (15.24 cm x 91.44 cm) *SSP 2314 Cherrywood and SSP 2316 Valley Oak Only
--------------	---

TESTING

Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Flammability:	ASTM E648	>.45 w/cm ²
Slip Resistance:	ASTM D2047	SCOF ≥0.6
Smoke Density:	ASTM E662	<450
Staining:	ASTM F925	Good
Resistance to Light:	ASTM F1515	ΔE<8
Resistance to Heat:	ASTM F1514	ΔE<8
Impact Sound Reductions:	ASTM E2179	ΔIIC 12

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Phthalate-Free
Indoor Air Quality:	FloorScore® Certification
Recyclability:	100% Recyclable through our ReStart® Program



- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.

