

ELEGANCE

WOOD - PRODUCT DATASHEET 2020



| TECHNICAL DATA (EN 13489) | | |
|--|--|-------------------------|
| Reaction to fire | EN 14342 Table 1 | Dfl-s1 |
| Emission of formaldehyde | EN 14342 | E1 |
| Brinell hardness (average value) Oak | (BHN) EN1534 | 3,7 |
| Taber Abraser/Lacquer's wear resistance Proteco Hardwax Oil | EN 13696 | N/A |
| Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II | NF EN ISO 140-8 / Acc to NF EN ISO 717-2 | 17 |
| Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II | EN ISO 10456:2007 | 0,152 0,182 0,192 |
| Thermal conductivity (W/m K) 22 mm | EN 12664 / EN 14342:2013 | 0,105 |
| Breaking strength | EN 1533 | 6480 N/600mm |
| Construction | 3-layer with softwood core | |

| INSTALLATION | | |
|---|--|--|
| Installation method | On beams or glue down | |
| Installation instruction | Download from www.tarkett.com Contact your supplier for more details | |
| Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system | Yes | |
| Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ² | | |

| RECOMMENDED ACCESSORIES | |
|--|--|
| Installation | Adhesive as recommended in installation instruction. Installation kit |
| Aesthetics | Skirting Transition moulding Pipe covers |
| Care & Maintenance | Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil |
| See more alternatives and the complete range of accessories @ www.tarkett.com | |

| DIMENSIONS & PACKAGE | 22x260x2520 | 22x280x2520 |
|--------------------------------|-------------|-------------|
| Thickness (mm) | 22 | 22 |
| Width (mm) | 260 | 280 |
| Length (mm) | 2520 | 2520 |
| Wear layer thickness (mm) | 4,0 | 4,0 |
| Boards/pack | 4 | 4 |
| m ² /pack | 2,62 | 2,82 |
| m ² /pallet | 31,44 | 33,84 |
| Net weight/m ² (kg) | 11,7 | 11,7 |

Due to the nature of the material this table shows typical values.

| MAINTENANCE |
|--|
| Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites. |
| See maintenance instructions @ www.tarkett.com |

Elegance Proteco Hardwax Oil

| | |
|--------------------------------------|---------------------|
| 99 % 99 % Natural Renewable | 100 % Recyclable |
|--------------------------------------|---------------------|



T&G



ELEGANCE

PRODUCT DATASHEET 2020

DESIGN

Oak planks made extra wide and extra long to enhance their natural look, mixing the smooth and more distinctive details of the wood. A light brushing emphasizes the design and authentic structure of the material. Perfect for special installations and commercial applications, where exclusivity and durability are the key requirements.

| PRODUCT DATA | Material code | Dimensions L x W x H (mm) | Pattern | Surface treatment | Surface effect | Bevel (4 side) | Stained | Latin name | DoP no. |
|------------------------|---------------|---------------------------|---------|---------------------|----------------|----------------|---------|------------|-----------|
| Elegance Oak Champagne | 41008005 | 2 520 x 260 x 22 | 1-strip | Protoco Hardwax Oil | Brushed | Minibevel | Yes | 1 | 0190-0116 |
| Elegance Oak Sterling | 41008004 | 2 520 x 280 x 22 | 1-strip | Protoco Hardwax Oil | Brushed | Minibevel | Yes | 1 | 0190-0116 |
| Elegance Oak | 41008001 | 2 520 x 280 x 22 | 1-strip | Protoco Hardwax Oil | Brushed | Minibevel | No | 1 | 0190-0116 |

1: Quercus Robur & Quercus Petraea



Elegance Oak Champagne



Elegance Oak Sterling



Elegance Oak

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com